

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)
- Other means of identification:**
Not relevant
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses (): Auxiliary product for the construction
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
PROPAMSA SAU
Ctra N-340 Km 1242,3
08620 Sant Vicenç dels Horts - España
Phone: +34 93 680 60 42
constructionsolutions@molins.es
molins.es
- 1.4 Emergency telephone number:** 0034 91 562 04 20

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
This product contains less than 1% of crystalline silica breathable fraction, so it does not require classification based on the provisions of Regulation (EU) 1272/2008 of the European Parliament and of the Council, of December 16, 2008, on classification, labeling and packaging of substances and mixtures, and amending and repealing Directives 67/548/EEC and 1999/45/EC and amending Regulation (EC) No 1907/2006.
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Eye Dam. 1: Serious eye damage, Category 1, H318
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1B: Sensitisation, skin, Category 1B, H317
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger

Hazard statements:
Eye Dam. 1: H318 - Causes serious eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1B: H317 - May cause an allergic skin reaction.
STOT SE 3: H335 - May cause respiratory irritation.
Precautionary statements:
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
P302+P352: IF ON SKIN: Wash with plenty of water.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
Substances that contribute to the classification
Cement Portland, Cr(VI) <2ppm
UFI: MD40-Q0G7-400Y-J2AP
- 2.3 Other hazards:**

- CONTINUED ON NEXT PAGE -

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Solution of additives, aggregates and cements

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 65997-15-1 EC: 266-043-4 Index: Not relevant REACH: Not relevant	Cement Portland, Cr(VI) <2ppm⁽¹⁾ Self-classified Regulation 1272/2008 Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1B: H317; STOT SE 3: H335 - Danger	10 - <25%
CAS: 1305-78-8 EC: 215-138-9 Index: Not relevant REACH: 01-2119475325-36-XXXX	Calcium oxide⁽²⁾ Self-classified Regulation 1272/2008 Eye Dam. 1: H318; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger	<1%

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity	Genus
Calcium oxide CAS: 1305-78-8 EC: 215-138-9	LD50 oral 2000 mg/kg LD50 dermal 2500 mg/kg LC50 inhalation dust Not relevant	Rat Rabbit

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

- CONTINUED ON NEXT PAGE -

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 4: FIRST AID MEASURES (continued)

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

The product is not flammable, it is not explosive, and does not enable or feed combustion in other materials

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Use in ventilated areas. Avoid the build up of dust

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

- CONTINUED ON NEXT PAGE -

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 7: HANDLING AND STORAGE (continued)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C
Maximum Temp.: 25 °C
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5. Keep the container tightly sealed and protected from open air and humidity.

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits	
Calcium oxide CAS: 1305-78-8 EC: 215-138-9		IOELV (8h)	1 mg/m ³
		IOELV (STEL)	4 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Calcium oxide CAS: 1305-78-8 EC: 215-138-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	4 mg/m ³	Not relevant	1 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Calcium oxide CAS: 1305-78-8 EC: 215-138-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	4 mg/m ³	Not relevant	1 mg/m ³

PNEC:

Identification					
Calcium oxide CAS: 1305-78-8 EC: 215-138-9	STP	2,27 mg/L	Fresh water	0,37 mg/L	
	Soil	817,4 mg/kg	Marine water	0,24 mg/L	
	Intermittent	0,37 mg/L	Sediment (Fresh water)	Not relevant	
	Oral	Not relevant	Sediment (Marine water)	Not relevant	

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

- CONTINUED ON NEXT PAGE -

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles (Filter type: P2/FFP2)		EN 149:2001+A1:2010 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.15 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2022	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2019

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0 % weight
V.O.C. density at 20 °C:	0 kg/m ³ (0 g/L)
Average carbon number:	Not relevant
Average molecular weight:	Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Solid
Appearance:	Powdery
Colour:	 Grey
Odour:	Odourless
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	Not relevant *
Vapour pressure at 20 °C:	Not relevant *
Vapour pressure at 50 °C:	Not relevant *
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	1400 kg/m ³
Relative density at 20 °C:	1,4
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	Not relevant *
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	375 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *

Explosive (Solid):

Lower explosive limit:	Not relevant *
Upper explosive limit:	Not relevant *

Particle characteristics:

Median equivalent diameter:	Not relevant *
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Aerosols-total percentage (by mass) of flammable components: Not relevant *

Other safety characteristics:

Surface tension at 20 °C: Not relevant *

Refraction index: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Avoid direct impact

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Incompatible	Silicate formation and calcium hydroxide	Not applicable	Not applicable	Base metal salts (Al, NH ₄ ,...)

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- IARC: Distillates (petroleum), solvent-dewaxed heavy paraffinic, < 3 % DMSO (> 7 cSt 40°C, < 20.5 cSt 40°C) (3: Not classifiable as to its carcinogenicity to humans)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Contact with human skin, without adequate protection, can result in skin thickening, cracking, or fissuring

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Calcium oxide CAS: 1305-78-8 EC: 215-138-9	LD50 oral	2000 mg/kg	Rat
	LD50 dermal	2500 mg/kg	Rabbit
	LC50 inhalation dust		

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Chronic toxicity:

Identification	Concentration		Species	Genus
Calcium oxide CAS: 1305-78-8 EC: 215-138-9	NOEC	Not relevant		
	NOEC	32 mg/L	Crangon septemspinosa	Crustacean

12.2 Persistence and degradability:

Not relevant

12.3 Bioaccumulative potential:

Not relevant

12.4 Mobility in soil:

- CONTINUED ON NEXT PAGE -

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 03 03*	inorganic wastes containing hazardous substances	Hazardous

Product - Cement that has exceeded its shelf life: 10 13 99

Product - Unused residue or dry spillage: 10 13 06

Product - after addition of water, hardened: 10 13 14, 17 01 01

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: *Calcium oxide (1305-78-8) - PT: (2, 3)*
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Not relevant

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

1. Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.
2. If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.
3. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there

- CONTINUED ON NEXT PAGE -

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 15: REGULATORY INFORMATION (continued)

is no possibility of contact with the skin.

Laboral exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2022/431, of the European Parliament and of the Council, of March 9, 2022, amending Directive 2004/37/EC, relating to the protection of workers against risks related to exposure to carcinogens or mutagens during work.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

· Removed substances

Quartz (1 % < RCS < 10%) (14808-60-7)

Texts of the legislative phrases mentioned in section 2:

H335: May cause respiratory irritation.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

STOT SE 3: Calculation method

Skin Irrit. 2: Calculation method

Eye Dam. 1: Calculation method

Skin Sens. 1B: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

PROPAM GROUT 140 HP
(Before PROPAM 140 STANDARD)

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -