

**PROPAM PUR**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** PROPAM PUR
- Other means of identification:**  
Not relevant
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses (): Coating, protection and decoration for exterior substrates.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
PROPAMSA SAU  
Ctra N-340 Km 1242,3  
08620 Sant Vicenç dels Horts - España  
Phone: +34 93 680 60 42  
constructionsolutions@molins.es  
molins.es
- 1.4 Emergency telephone number:** 0034 91 562 04 20

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Eye Irrit. 2: Eye irritation, Category 2, H319  
Flam. Liq. 3: Flammable liquids, Category 3, H226  
Resp. Sens. 1: Sensitisation, respiratory, Category 1, H334  
Skin Irrit. 2: Skin irritation, Category 2, H315  
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Danger**
- 
- Hazard statements:**  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Skin Irrit. 2: H315 - Causes skin irritation.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements:**  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260: Do not breathe vapours  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P501: Dispose of contents/ container in accordance with local/regional/national/international regulation.
- Supplementary information:**  
EUH204: Contains isocyanates. May produce an allergic reaction.
- UFI:** STS2-Y02R-P001-K4A8
- 2.3 Other hazards:**  
Product does not meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product does not meet the criteria.  
In normal use conditions and in its original form, the product does not have any other risk for health and the environment.

- CONTINUED ON NEXT PAGE -

**PROPAM PUR**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**

Not relevant

**3.2 Mixture:**

**Chemical description:** Polyurethane resin

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(1)</sup></b>	ATP CLP00	<b>10 - &lt;25%</b>
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	
CAS: Not relevant EC: 905-562-9 Index: Not relevant REACH: 01-2119555267-33-XXXX	<b>Reaction mass of ethylbenzene and m-xylene and p-xylene<sup>(1)</sup></b>	Self-classified	<b>10 - &lt;25%</b>
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**Other information:**

Identification	Specific concentration limit
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9	% (w/w) >=10: STOT RE 2 - H373

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	Not relevant	
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	17 mg/L	Rat
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9	LD50 oral	Not relevant	
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation vapour	11 mg/L	

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

- CONTINUED ON NEXT PAGE -

**PROPAM PUR**

**SECTION 4: FIRST AID MEASURES (continued)**

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Not relevant

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

**Unsuitable extinguishing media:**

Water jet

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

**6.4 Reference to other sections:**

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -

**PROPAM PUR**

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Specific storage requirements

Minimum Temp.: 5 °C  
Maximum Temp.: 25 °C  
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits		
Xylene <sup>(1)</sup> CAS: 1330-20-7 EC: 215-535-7		IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
		IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9		IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
		IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>

<sup>(1)</sup> Skin

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>

**DNEL (General population):**

- CONTINUED ON NEXT PAGE -

**PROPAM PUR**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>

**PNEC:**

Identification			
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water
	Soil	2,31 mg/kg	Marine water
	Intermittent	0,327 mg/L	Sediment (Fresh water)
	Oral	Not relevant	Sediment (Marine water)
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9	STP	6,58 mg/L	Fresh water
	Soil	2,31 mg/kg	Marine water
	Intermittent	0,327 mg/L	Sediment (Fresh water)
	Oral	Not relevant	Sediment (Marine water)


**8.2 Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	 CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	 CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield	 CAT II	EN 166:2002 UNE-EN ISO 18526-1 al 4:2020 UNE-EN ISO 18526-1 al 4:2020 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

- CONTINUED ON NEXT PAGE -



**PROPAM PUR**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	 CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2005/A1:2011 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1995	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	 CAT III	EN ISO 13287:2020 EN ISO 20345:2022 EN 13832-1:2019	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	15 % weight
V.O.C. density at 20 °C:	212 kg/m <sup>3</sup> (212 g/L)
Average carbon number:	8
Average molecular weight:	106,2 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	184 kg/m <sup>3</sup> (184 g/L)
EU limit for the product (Cat. A.I):	500 g/L (2010)
Components:	Not relevant

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	According to the markings on the package
Odour:	Characteristic
Odour threshold:	Not relevant *

**Volatility:**

Boiling point at atmospheric pressure:	Not relevant *
Vapour pressure at 20 °C:	Not relevant *
Vapour pressure at 50 °C:	4128,99 Pa (4,13 kPa)
Evaporation rate at 20 °C:	Not relevant *

**Product description:**

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**PROPAM PUR**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Density at 20 °C:	1400 kg/m <sup>3</sup>
Relative density at 20 °C:	Not relevant *
Dynamic viscosity at 20 °C:	4000 mPa·s
Kinematic viscosity at 20 °C:	2816,9 mm <sup>2</sup> /s
Kinematic viscosity at 40 °C:	>20,5 mm <sup>2</sup> /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Soluble in organic solvents
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

**Flammability:**

Flash Point:	35 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	Not relevant *
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *

**Particle characteristics:**

Median equivalent diameter:	Not relevant *
-----------------------------	----------------

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

**Other safety characteristics:**

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

- CONTINUED ON NEXT PAGE -



**PROPAM PUR**

**SECTION 10: STABILITY AND REACTIVITY (continued)**

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Causes serious eye irritation.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Xylene (3: Not classifiable as to its carcinogenicity to humans); Reaction mass of ethylbenzene and m-xylene and p-xylene (3: Not classifiable as to its carcinogenicity to humans); Toluene Diisocyanate (2B: Possibly carcinogenic to humans)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Prolonged exposure can result in specific respiratory hypersensitivity.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -



**PROPAM PUR**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	3523 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	17 mg/L	Rat
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9	LD50 oral	5627 mg/kg	Mouse
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation vapour	11 mg/L	

**11.2 Information on other hazards:**

**Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

**Other information**

Not relevant

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect.  
For more information see section 3.

**12.1 Toxicity:**

**Chronic toxicity:**

Identification	Concentration		Species	Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	88 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9	BCF	9
	Pow Log	2.77
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Not relevant	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

- CONTINUED ON NEXT PAGE -

**PROPAM PUR**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Product does not meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product does not meet the criteria.

**12.7 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

**Type of waste (Regulation (EU) No 1357/2014):**

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2025 and RID 2025:



- 14.1 UN number or ID number:** UN1139
- 14.2 UN proper shipping name:** COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)
- 14.3 Transport hazard class(es):** 3
- Labels:** 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: Not relevant
- Tunnel restriction code: D/E
- Physico-Chemical properties: see section 9
- Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by sea:**

With regard to IMDG 42-24:

- CONTINUED ON NEXT PAGE -

**PROPAM PUR**

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number or ID number:** UN1139  
**14.2 UN proper shipping name:** COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)  
**14.3 Transport hazard class(es):** 3  
**Labels:** 3  
**14.4 Packing group:** III  
**14.5 Marine pollutant:** No  
**14.6 Special precautions for user**  
Special regulations: 955  
EmS Codes: F-E, S-E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Not relevant  
**14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2025:



- 14.1 UN number or ID number:** UN1139  
**14.2 UN proper shipping name:** COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)  
**14.3 Transport hazard class(es):** 3  
**Labels:** 3  
**14.4 Packing group:** III  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
Physico-Chemical properties: see section 9  
**14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000,000	50000,000

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

- CONTINUED ON NEXT PAGE -

## SECTION 15: REGULATORY INFORMATION (continued)

### Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

### Texts of the legislative phrases mentioned in section 2:

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H373: May cause damage to organs through prolonged or repeated exposure.

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

### Classification procedure:

Flam. Liq. 3: Calculation method (2.6.4.3)

Skin Irrit. 2: Calculation method

Eye Irrit. 2: Calculation method

Resp. Sens. 1: Calculation method

STOT RE 2: Calculation method

### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

### Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

**PROPAM PUR**

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -