



VALVES

SIGHT BALL VALVE MINI

BOSTON



100% tightness

Reliability



The ball valve Boston mini is designed and guaranteed for the use in installations of potable water, warm water, and compressed air networks. For fuels, solvents, acids, and aggressive liquids, consult us.



This range offers a maximum protection against the corrosion due to the nickel-plating coating (except for the inside of the body, fitting, and the free nut valves). The nickel coating enables the installation outdoors without impairing its performance.

As they are manufactured by hot stamping, against other valves obtained via foundry, the absence of pores and a higher mechanical resistance is achieved.



TECHNICAL DATA	
Maximum pressure	25 bar
Maximum temperature	90 °C
Range of temperature	-20 °C to 90 °C

MATERIALS	
Body and fitting	Brass (UNE-EN 12164 - 12165)
Ball	Brass (UNE-EN 12164 - 12165)
Stem and press	Brass (UNE-EN 12164 - 12165)
Sealing	PTFE
O ring	NBR
Handle	Aluminium
Body finish	Polished or shot blasting

MINI H-H Published

 				
Code	Ø	A	B	h
35520	1/4"	40.5	32.8	26.5
35221	3/8"	41.5	32.8	26.2
35522	1/2"	44.5	32.8	28.2

MINI H-H Published

				
Code	Ø	A	B	h
35525	1/4"	40.5	32.8	26.5
35226	3/8"	41.5	32.8	26.2
35527	1/2"	44.5	32.8	28.2
35528	3/4"	52.5	32.8	31.2





VALVES



SIGHT BALL VALVE MINI

BOSTON

MINI M-H Polished

				
				
Code	Ø	A	B	h
35530	1/4"	39.3	32.8	26.5
35531	3/8"	40.5	32.8	26.2
35532	1/2"	44.5	32.8	28.2

MINI M-H Polished

				
				
Code	Ø	A	B	h
35535	1/4"	39.3	32.8	26.5
35536	3/8"	40.5	32.8	26.2
35537	1/2"	44.5	32.8	28.2
35538	3/4"	52.5	32.8	31.2

RED HANDLE

	
Código	
35173	

BLUE HANDLE

	
Código	
35171	