

## General description

The kit square foot is designed to support metallic structures (H-frames) on roofs or in industrial spaces. Suitable for 41 x 41 mm slotted channel rails.

- Designed to fit STRUT channel (not supplied)
- Preserves the waterproofing membrane of the roof
- Easy and fast installation
- Closed cell polyethylene anti-vibration pads pre-attached
- Great flexibility: adjustable height / weight
- Suitable for 41 x 41 mm slotted channel rails

| SQUARE FOOT : B-SQF   | H FRAME KIT : B-KSF   |
|---|---|
|    |   |
| <p>The square foot includes :</p> <ul style="list-style-type: none"> <li>• High Density Polyethylene (HDPE) foot</li> <li>• Pre-attached insulating mats</li> </ul> | <p>The H frame kit includes :</p> <ul style="list-style-type: none"> <li>• Square foot : x2</li> <li>• M10 brackets : x2</li> <li>• M10 fixings : x4</li> </ul> |

## Technical specification

|                                       | B-SQF-200                        | B-SQF-305          | B-SQF-500          |
|---------------------------------------|----------------------------------|--------------------|--------------------|
| <b>Material</b>                       | High Density Polyethylene (HDPE) |                    |                    |
| <b>Dimensions</b>                     | 200 x 200 x 120 mm               | 305 x 305 x 120 mm | 500 x 500 x 120 mm |
| <b>Maximum load per set of 2 feet</b> | 150 Kg*                          | 350 Kg*            | 500 Kg*            |
| <b>Recommended temperature</b>        | -30°C / +110°C                   |                    |                    |

\* The support rails not being supplied by us, loads are given for information. Please refer to the technical data of rails to know the maximum load.

## Application

Designed to support ventilation ducts, cables trays, pipes.

