

DISCO



Product characteristics

Body

PET acoustic panel and steel sheet/extruded aluminium profile

Finish

Epoxy polyester powder coated

Optical system

bOPTICS - Symmetric reflector
PB - Shiny reflector

Light source

LED, RG1, CRI >80, MacAdam Step ≤3

LED lifetime

bOPTICS: 80.000h @ L90, B10, Ta 25°C
PB: 60.000h @ L80, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz



IP 20


650°C

01. Select version



DISCO M01


Spot



Downlight




bOPTICS - Symmetric reflector | PB - Shiny reflector - 20°



TYPE	W	lm output	lm/W	Dmm	CODE*
Spot	33	3029	92	Ø700	90972L700▼▲◆0◆03
Spot	42	3783	90	Ø900	90972L900▼▲◆0◆03
Downlight	33	3029	92	Ø700	90972L700▼▲◆0◆05
Downlight	42	3783	90	Ø900	90972L900▼▲◆0◆05

bOPTICS - Symmetric reflector | PB - Shiny reflector - 50°



TYPE	W	lm output	lm/W	Dmm	CODE*
Spot	33	2994	91	Ø700	90972L700▼▲◆0◆04
Spot	42	3738	89	Ø900	90972L900▼▲◆0◆04
Downlight	33	2994	91	Ø700	90972L700▼▲◆0◆06
Downlight	42	3738	89	Ø900	90972L900▼▲◆0◆06


*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H


Colour

Colour	
Black	B
Anthracite	A
Cedar	R
Stone	I
Carrara	E
Seashell	O
Sand	S
Arena	3
Chocolat	C
Sacramento	N
Moss	M
Citron	V
Desert	L
Olive	D
Mustard	T
Blush	5
Ochre	H
Terracotta	7
Tiger	Y
Raspberry	K
Wine	X
Rosewood	J
Navy	F
Cobalt	U
Cornflower	1
Pacific	P
Belize	Z
Lilac	2
Ice	G
White	W

DISCO M02




bOPTICS - Symmetric reflector




W	lm output	lm/W	Dmm	CODE*
21	1491	71	Ø700	90972L700▼▲◆0◆01
30	2237	75	Ø900	90972L900▼▲◆0◆01

DISCO M03



bOPTICS - Symmetric reflector



W	lm output	lm/W	Dmm	CODE*
21	1491	71	Ø700	90972L700▼▲◆0◆02
30	2237	75	Ø900	90972L900▼▲◆0◆02

Colour temp.	
3000K	3
4000K	0

DISCO

• To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.

03. Select options

OPTIONS		Code*
Suspension		
S15 L1500 mm (x4)		913303
S15 L3000 mm (x4)		913304
S15 L6000 mm (x4)		913305
Transparent current supply cable		
L1500 mm - 3 x 0,75 mm ²		940400
L1500 mm - 5 x 0,75 mm ²		940500
L3000 mm - 3 x 0,75 mm ²		940401
L3000 mm - 5 x 0,75 mm ²		940501
L6000 mm - 3 x 0,75 mm ²		940402
L6000 mm - 5 x 0,75 mm ²		940502
Ceiling rose		
Surface mounted T41	45  Ø50	978805♣
Recessed T42	 Ø40 32  Ø50	978804♣



*Replace the symbols to complete the code

Colour	
☐ White	W
☒ Black	B



Product details



Model M01



Model M02



Model M03



bOPTICS diffuser



Downlights



Adjustable spotlight



Acoustic panel



Acoustic panel (macro)



Ceiling rose

