

ELI 50 Spot /E 1



Product characteristics

Body Aluminium
Finish Powder coated
Optical system PB - Shiny reflector
Light source LED, RG1, CRI>90, MacAdam Step ≤3
LED lifetime 60.000h @ L80, B10, Ta 25°C
Control gear Not included
Ceiling thickness For ceilings between 1-25 mm

90° tilt + 355° rotation

ELI 50 Spot /E 2



Product characteristics

Body Aluminium
Finish Powder coated
Optical system PB - Shiny reflector
Light source LED, RG1, CRI>90, MacAdam Step ≤3
LED lifetime 60.000h @ L80, B10, Ta 25°C
Control gear Not included
Ceiling thickness For ceilings between 1-25 mm

	
	
	
	

01. Select version



ELI 50 Spot / E 2

PB - Shiny reflector - 20°

W	lm output	lm/W	mA		CODE*
10	1494	149	300	Ø45x105	90946L0020▲0◆20
17	2336	137	500	Ø45x105	90945L0020▲0◆20

PB - Shiny reflector - 50°

W	lm output	lm/W	mA		CODE*
10	1448	145	300	Ø45x105	90946L0020▲0◆50
17	2288	135	500	Ø45x105	90945L0020▲0◆50

ELI 50 Spot / E 2

•To complete the product add the control gear. Please order separately.

*Replace the symbols to complete the code

Colour

☐ White

☐ Black

▲

W

B

Colour temp.

◆

3000K

4000K

B

A

02. Select options

OPTIONS	Code
Control gear HF	
Driver 12,6W 10-42V 300mA HF	900003E
Driver 21W 10-42V 500mA HF	900007E
Control gear dimmable DALI	
Driver 15,6W 09-52V 300mA DALI+ PUSH	900103H
Driver 26W 09-52V 500mA DALI+ PUSH	900107H
Steel safety cable	
L1500 mm	955010