

TUBULAR
LUMINAIRES

TTP 50 360 HRZ



Product characteristics

Body

Polycarbonate tube

Finish

Powder coated aluminium
end caps

Optical system

TOP - Opal diffuser

Light source

LED, RG0, CRI>80, MacAdam Step ≤ 3

LED lifetime

70.000h @ L80, B10, Ta 25°C

Control gear


Not included




01. Select version



TTP 50 360 HRZ



TOP - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
10	912	91	572	90677L0600♣0♦00
18	1685	94	972	90677L0900♣0♦00
23	2275	99	1272	90677L1200♣0♦00
29	2916	101	1572	90677L1500♣0♦00

*Replace the symbols to complete the code

Colour	♣
□ White	W
■ Grey	G
■ Black	B


Colour temp.	♦
3000K	3
4000K	0

TTP 50 360 HRZ

• To complete the product add the suspension, current supply cable and ceiling rose. Please order separately.

02. Select ceiling rose

Recessed - T31 D90



Ø70


HF

L572, L972, L1272, L1572 **CODE***
972750♣

DALI

L572, L972, L1272, L1572 **CODE***
972752♣

Surface mounted - T36 L350W50



HF

L572, L972, L1272, L1572 **CODE***
972770♣

DALI

L572, L972, L1272, L1572 **CODE***
972772♣

CEILING ROSE

- Control gear included in the ceiling rose.

03. Select options

OPTIONS Code

Suspension

- For recessed ceiling rose T31 D90:

S4 L1500 mm (x2) **910200**
S4 L3000 mm (x2) **910204**
S4 L6000 mm (x2) **910208**

- For surface ceiling rose T36 L350W50:

S13 L1500 mm (x2) **913200**
S13 L3000 mm (x2) **913201**
S13 L6000 mm (x2) **913202**

Transparent current supply cable

L1500 mm - 2 x 0,75 mm² **942800**
L3000 mm - 2 x 0,75 mm² **942801**
L6000 mm - 2 x 0,75 mm² **942802**



*Replace the symbols to complete the code


Colour ♣
 White W
 Black B



Product details



Suspension



Ceiling roses

