



Architectural
lighting

NOAH



NOAH
62



NOAH /D
68








Scale 1:1

DAZ - Opal diffuser



NOAH



Product characteristics

Body

Wood

Finish

Shiny rosewood

Optical system

DAZ - Opal diffuser

Wiring

Transparent current supply cable with
1500 mm included

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

65.000h @ L90, B10, Ta 25°C

Control gear

Not included



230V/50Hz




IP 40

650°C

01. Select version




NOAH



20 l

Ø650

DAZ - Opal diffuser



150° 350° 150°
120° 210° 120°
90° 140° 90°
70°
C0 - C180 —
C90 - C270 - -

W

35

lm output

5273

lm/W

135

CODE*

90061L0360J0♦00

*Replace the symbols to complete the code

Colour temp.

♦

3000K

3

4000K



0

NOAH

• To complete the product add suspension and ceiling rose. Please order separately.

63

02. Select ceiling rose

Trimless		Surface mounted	
			
HF		HF	
Ø650	CODE* 974810♣	Ø650	CODE* 974910♣
DALI		DALI	
Ø650	CODE* 973010♣	Ø650	CODE* 973210♣
BLUETOOTH		BLUETOOTH	
Ø650	CODE* 972910♣	Ø650	CODE* 973110♣
CEILING ROSE			
• Control gear included in the ceiling rose.			



*Replace the symbols to complete the code

Colour	♣
□ White	W
■ Black	B

03. Select options

OPTIONS	Code
Suspension S10 L1500 mm (x3)	9111001



Select options



Shiny rosewood finishing



Suspended application



Diffuser DAZ



Finishing detail



Trimless recessed ceiling rose



Surface mounted ceiling rose



Adjustable table lamp





1. 20° tiltable

The product allows tilting up to 20° in all directions, which provides versatility to direct the light as you desire.

2. TouchDIM button

The TouchDIM button allows you to turn-on or turn-off the product and adjust the light intensity easily and intuitively.



NOAH /D



Product
characteristics

Body Steel sheet base Upper part in wood	
Finish Black powder coated Upper part in shiny rosewood	
Optical system DAZ - Opal diffuser	
Wiring Black current supply cable with 1500 mm and electrical plug type F included	
Light source LED, RG1, CRI>90, MacAdam Step ≤3	
LED lifetime 60.000h @ L80, B10, Ta 25°C	
Control gear 24V transformer included	

CE	RoHS
24V DC	III
IP 40	650°C

01. Select version



NOAH /D

26 l

356

Ø250

DAZ - Opal diffuser

CO - C180 —
C90 - C270 - -

W

5

lm output

307

lm/W

61

CODE*

90306L009HJ0♦00

*Replace the symbols to complete the code

Colour temp.

2700K

4000K

♦

2

0

NOAH /D

•The standard product is supplied with TouchDIM button.

Select options

Shiny rosewood finishing

TouchDIM button

Adjustable

Finishing detail

Electrical plug type F

69