



**Battens and
track systems**

PAS



PAS
782



PAS Line
784





**Product
characteristics**

Body

Extruded aluminium profile

Finish

Powder coated

Optical system

Lens

Light source



4000K LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L80, B10, Ta 25°C


Control gear

LED driver 220-240V-50/60Hz included




01. Select version

PAS




Symmetric lens | Beam angle of 90°



W	lm output	lm/W	Lmm	CODE*
50	8050	161	1436	90770L005♥♣♦000
59	9338	158	1436	90771L005♥♣♦000
100	16100	161	2871	90770L010♥♣♦000
118	18676	158	2871	90771L010♥♣♦000

Asymmetric lens



W	lm output	lm/W	Lmm	CODE*
50	7963	159	1436	90772L005♥♣♦000
59	9237	157	1436	90773L005♥♣♦000
100	15925	159	2871	90772L010♥♣♦000
118	18473	157	2871	90773L010♥♣♦000



*Replace the symbols to complete the code

Control gear	▼
HF	E
DALI	H

Colour	▲
□ White	W
■ Grey	G

Emergency	●
No EM	0
EM 3h (K3) ¹	3

PAS

- In the L2871 mm emergency version, only half the luminaire will run on emergency.

02. Select options

OPTIONS Code

Current supply cable

- Under request.

Suspension

Fixing clamps for threaded rod (x2)	910102
Fixing clamps + pigtail hooks (x2)	910101
Fixing clamps + height-adjustable cables (x2)	910103
Fixing clamps + hook for wire suspensions (x2)	910100



Product details



Suspensions

¹ Prepared for emergency remote control.

PAS Line



Product characteristics


Body
Extruded aluminium profile
Finish
Powder coated
Optical system
Lens
Light source
4000K LED, RG1, CRI>80, MacAdam Step ≤3
LED lifetime
80.000h @ L80, B10, Ta 25°C
Control gear
LED driver 220-240V-50/60Hz included

CE	RoHS
230V/50Hz	
⏚	IP 20
650°C	


01. Select version



PAS Line




Symmetric lens | Beam angle of 90°



W	lm output	lm/W	Lmm	CODE*
50	8050	161	1435	90774L005♥♣♦000
59	9338	158	1435	90775L005♥♣♦000
100	16100	161	2870	90774L010♥♣♦000
118	18676	158	2870	90775L010♥♣♦000

Asymmetric lens



W	lm output	lm/W	Lmm	CODE*
50	7963	159	1435	90776L005♥♣♦000
59	9237	157	1435	90777L005♥♣♦000
100	15925	159	2870	90776L010♥♣♦000
118	18473	157	2870	90777L010♥♣♦000

*Replace the symbols to complete the code

Control

gear

HF	E
DALI	H
HF Three-phase	R
DALI Three-phase	S

Colour

☐ White	W
☐ Grey	G

Emergency

No EM	0
EM 3h (K3) ¹	3

PAS Line

- For suspended version add the suspension. Please order separately.
- To complete the line add the start kit, through-wiring and body connector kit. Please order separately.
- In the L2870 mm emergency version, only half the luminaire will run on emergency.
- Dimensions do not include start kit. To complete the line add 1 mm to the length.
- The maximum line length with 1 single feeding point is 30000 mm.

¹ Prepared for emergency remote control.

02. Select options

OPTIONS	Code*
Start kit - end cap start/end	
White	921500
Grey	921501
• 2 end caps included.	
Through-wiring	
3 x 1,5 mm ²	945660
5 x 1,5 mm ²	945760
7 x 1,5 mm ²	946060
9 x 1,5 mm ²	948660
11 x 1,5 mm ²	948860
Body connector kit	
• Steel body connector.	
930800	
Current supply cable	
• Under request.	
Suspension	
Fixing clamps for threaded rod (x2)	910102
Fixing clamps + pigtail hooks (x2)	910101
Fixing clamps + height-adjustable cables (x2)	910103
Fixing clamps + hook for wire suspensions (x2)	910100
Blank part	
L1500 mm	992600♣
L3000 mm	992601♣
Bespoke projects	
• Under request.	



*Replace the symbols to complete the code

Colour	♣
☐ White	W
☐ Grey	G



Product details



Suspensions

