



Technical
lighting

TEI



TEI
638





**Product
characteristics**


Body
Steel sheet
Finish
White matte powder coated
Fixing system
Pull-up: for plasterboard ceilings with brackets
Optical system
DCS - Microperforated diffuser
Light source
LED, RG1, CRI>80, MacAdam Step ≤3
LED lifetime
80.000h @ L90, B10, Ta 25°C
Control gear
LED driver 220-240V-50/60Hz included
Ceiling thickness
For ceilings between 1-25 mm

CE	RoHS
230V/50Hz	
⏚	IP 20
650°C	⚡


01. Select version



TEI



DCS - Microperforated diffuser



UGR	W	lm output	lm/W	Beam	CODE*
≤19	29	2223	77	578x578	90853L060▼W●●●
≤22	43	3334	78	578x578	90852L060▼W●●●

*Replace the symbols to complete the code

Control gear	▼
HF	E
DALI	H

Emergency	●
No EM	0
EM 3h (K3) ¹	3

Colour temp.	◆
3000K	3
4000K	0

Connector	♣
No connector	00
W3M ²	W3
W5MD ³	W5

02. Select options

OPTIONS Code

Steel safety cable

L1500 mm 955000

Bespoke projects

- Under request.

¹ Prepared for emergency remote control.

² 3-pole Wieland GST18i3 male connector.

³ 5-pole Wieland GST18i5 DIM male connector.