





Tubular
luminaires

TTP 50 360



TTP 50 360 HRZ
734



TTP 50 360 VRT
738



TTP 50 360 HRZ



Product characteristics

Body

Polycarbonate tube

Finish

Powder coated aluminium
end caps

Optical system

TOP - Opal diffuser

Light source

LED, RG0, CRI>80, MacAdam Step ≤3

LED lifetime

70.000h @ L80, B10, Ta 25°C

Control gear


Not included




01. Select version



TTP 50 360 HRZ



TOP - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
10	912	91	572	90677L0600◆0◆00
18	1685	94	972	90677L0900◆0◆00
23	2275	99	1272	90677L1200◆0◆00
29	2916	101	1572	90677L1500◆0◆00
34	3370	99	1872	90677L1800◆0◆00
37	3744	101	2072	90677L2000◆0◆00

*Replace the symbols to complete the code


Colour	◆
□ White	W
■ Grey	G
■ Black	B

Colour temp.	◆
3000K	3
4000K	0

TTP 50 360 HRZ

• To complete the product add the suspension, current supply cable and ceiling rose. Please order separately.

02. Select ceiling rose

Recessed - T31 D90		Surface mounted - T36 L350W50	
			
HF		HF	
CODE*		CODE*	
L572, L972, L1272, L1572	972750♣	L572, L972, L1272, L1572	972770♣
L1872, L2072	972751♣	L1872, L2072	972771♣
DALI		DALI	
CODE*		CODE*	
L572, L972, L1272, L1572	972752♣	L572, L972, L1272, L1572	972772♣
L1872, L207	972753♣	L1872, L2072	972773♣
CEILING ROSE			
• Control gear included in the ceiling rose.			



*Replace the symbols to complete the code

Colour	
□ White	W
■ Black	B

03. Select options

OPTIONS	Code
Suspension	
• For recessed ceiling rose T31 D90:	
S4 L1500 mm (x2)	910200
S4 L3000 mm (x2)	910204
S4 L6000 mm (x2)	910208
• For surface ceiling rose T36 L350W50:	
S13 L1500 mm (x2)	913200
S13 L3000 mm (x2)	913201
S13 L6000 mm (x2)	913203
Transparent current supply cable	
L1500 mm - 2 x 0,75 mm ²	942800
L3000 mm - 2 x 0,75 mm ²	942801
L6000 mm - 2 x 0,75 mm ²	942802



Product details



Suspension



Ceiling roses



TTP 50 360 VRT



Product
characteristics

Body

Polycarbonate tube

Finish

Powder coated aluminium
end caps

Optical system

Polycarbonate

Light source

LED, RG0, CRI>80, MacAdam Step ≤3

LED lifetime

70.000h @ L80, B10, Ta 25°C

Control gear


Not included




01. Select version



TTP 50 360 VRT



TOP - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
10	912	91	570	90555L0600▲0◆00
18	1685	94	970	90555L0900▲0◆00
23	2275	99	1270	90555L1200▲0◆00
29	2916	101	1570	90555L1500▲0◆00
34	3370	99	1870	90555L1800▲0◆00
37	3744	101	2070	90555L2000▲0◆00

*Replace the symbols to complete the code


Colour	▲
□ White	W
■ Grey	G
■ Black	B

Colour temp.	◆
3000K	3
4000K	0

TTP 50 360 VRT

• To complete the product add the suspension, current supply cable and ceiling rose. Please order separately.

Surface mounted - T32 D80



Colour	
☐ White	W
☒ Black	B

HF

	CODE*
L572, L972, L1272, L1572	972760♠
L1872, L2072	972761♠

DALI

	CODE*
L572, L972, L1272, L1572	972762♠
L1872, L2072	972763♠

- Control gear included in the ceiling rose.

Product details

Code

L1500 mm - 2 x 0,75 mm ²	942800
L3000 mm - 2 x 0,75 mm ²	942801
L6000 mm - 2 x 0,75 mm ²	942802

- Under request.



Ceiling roses

