

6th ELEMENT



Product characteristics

Body

Die-cast aluminium



Finish

Powder coated



Optical system

Lens



Light source

LED, RG1, CRI>90, MacAdam Step ≤3

LED lifetime

50.000h @ L80, B10, Ta 25°C


Control gear

Not included


01. Select version



6th ELEMENT




50° lens | Direct / Indirect (50%/50%)




UGR	W	lm output	lm/W	mA	CODE*
≤10	17	2232	131	500	90280L0160▲0◆50

80° lens | Direct / Indirect (50%/50%)




UGR	W	lm output	lm/W	mA	CODE*
≤19	17	2158	127	500	90280L0160▲0◆80

50° lens | Direct



UGR	W	lm output	lm/W	mA	CODE*
≤13	9	1128	125	250	90328L0090▲0◆50
≤13	12	1512	126	350	90328L0160▲0◆50

80° lens | Direct



UGR	W	lm output	lm/W	mA	CODE*
≤25	9	1091	121	250	90328L0090▲0◆80
≤25	12	1428	119	350	90328L0160▲0◆80

*Replace the symbols to complete the code

Colour	Symbol
White	W
Black	B
Rusty chain	R


Colour temp.	Symbol
3000K	B
4000K	A

6th ELEMENT

• To complete the product add suspension, current supply cable and ceiling rose. Please order separately.

02. Select ceiling rose

Recessed - T12 Q200



135x135

HF

	CODE*
10,5W 10-42V 250mA HF	971810♣
14,7W 10-42V 350mA HF	971811♣
21W 10-42V 500mA HF	971812♣

DALI

	CODE*
13W 09-52V 250mA DALI	971820♣
18,2W 09-52V 350mA DALI	971821♣
26W 09-52V 500mA DALI	971822♣

Surface mounted - T53 D120



HF

	CODE*
10W 30-42V 250mA HF	971830♣
15W 26-43V 350mA HF	971831♣
21W 30-42V 500mA HF	971832♣

DALI

	CODE*
12W 03-45V 250mA DALI	971840♣
16W 03-45V 350mA DALI	971841♣
20W 03-40V 500mA DALI	971842♣

CEILING ROSE

- The recessed ceiling rose T12 Q200 is class II.
- The surface ceiling rose T53 D120 is class I.
- Control gear included in the ceiling rose.

03. Select options

OPTIONS Code

Suspension

S14 L1500 mm (x3)	913300
S14 L3000 mm (x3)	913301
S14 L6000 mm (x3)	913302

Current supply cable

L1500 mm - 2 x 0,75 mm ²	942800
L3000 mm - 2 x 0,75 mm ²	942801
L6000 mm - 2 x 0,75 mm ²	942802



*Replace the symbols to complete the code

Colour	♣
□ White	W
■ Black	B
■ Rusty chain	R




Select options



Light effect with 50° lens



Light effect with 80° lens



Ceiling roses

