



**Product characteristics**

---

**Body**  
Steel sheet

**Frame**  
Aluminium

**Finish**  
White matte powder coated

**Wiring**  
Pre-wired with 1000 mm long  
H05VV-F cable

**Optical system**  
Narrow - narrow beam angle  
Medium - medium beam angle  
Wide - wide beam angle

**Light source**  
4000K LED, RG1, CRI>80, MacAdam Step  $\leq 3$

**LED lifetime**  
80.000h @ L80, B10, Ta 25°C

**Control gear**  
LED driver 220-240V-50/60Hz included


---




01. Select version



CAB




**NARROW - narrow beam angle**




W	lm output	lm/W	LxWmm	CODE*
68	11206	165	676x365	90849L063▼W●000
136	22411	165	1250x365	90849L123▼W●000
182	29882	164	1250x470	90849L124▼W●000

**MEDIUM - medium beam angle**



W	lm output	lm/W	LxWmm	CODE*
68	11206	165	676x365	90850L063▼W●000
136	22411	165	1250x365	90850L123▼W●000
182	29882	164	1250x470	90850L124▼W●000

**WIDE - wide beam angle**



W	lm output	lm/W	LxWmm	CODE*
68	11327	167	676x365	90851L063▼W●000
136	22655	167	1250x365	90851L123▼W●000
182	30206	166	1250x470	90851L124▼W●000

\*Replace the symbols to complete the code

**Control gear**

HF	E
DALI	H

**Emergency**


No EM	0
EM 3h (K3) <sup>1</sup>	3

CAB

• To complete the product add the fixing system. Please order separately.

<sup>1</sup> Prepared for emergency remote control.

## 02. Select options

OPTIONS	Code
<b>Connector kit</b>	
Kit 3-pole IP68 connector	966300
Kit 5-pole IP68 connector	966400
<b>Surface mounting kit</b>	
Fixing brackets and screws included (x2)	925701
<b>Ceiling adjustable mounting kit</b>	
Fixing brackets and screws included (x2)	925700
<b>Suspension</b>	
Pigtail bracket kit (x4)	911200
Anchor bracket kit (x4)	911202
Wire bracket kit (x2)	911203
<b>Recessed mounting kit</b>	
676x365 mm	925702
1250x365 mm	925703
1250x470 mm	925704
<ul style="list-style-type: none"> <li><input type="checkbox"/> 725x412</li> <li><input type="checkbox"/> 1300x412</li> <li><input type="checkbox"/> 1300x518</li> </ul>	
<b>Steel safety cable</b>	
L1500 mm	955000
<b>Light and presence sensor</b>	
• Under request.	
<b>Low Output version</b>	
• Under request.	



### Product details



Surface mounting kit



Ceiling adjustable mounting kit



Suspensions



Recessed mounting kit

