

DYNA



### Product characteristics

#### Body

Aluminium

#### Finish

Powder coated

#### Optical system

EFFICIENT - High performance matte reflector

CONTROL - Glare control matte reflector

#### Light source

LED, RG1, CRI>80, MacAdam Step  $\leq 3$

#### LED lifetime

60.000h @ L70, B10, Ta 25°C

#### Control gear

Not included

#### Ceiling thickness


For ceilings between 1-25 mm




## 01. Select version



### DYNA



#### EFFICIENT - High performance matte reflector | Beam angle of 80°




UGR	W	lm output	lm/W	mA	Φ	CODE*
≤19	8	1172	145	250	Ø220	90014L00L0♣0♦00
≤19	17	2283	135	500	Ø220	90014L00M0♣0♦00
≤22	24	3096	128	700	Ø220	90014L00H0♣0♦00


\*Replace the symbols to complete the code

Colour	Symbol
White	W
Black	B

Colour temp.	Symbol
3000K	3
4000K	0



#### CONTROL - Glare control matte reflector | Beam angle of 80°



UGR	W	lm output	lm/W	mA	Φ	CODE*
≤16	8	1125	139	250	Ø220	90123L00L0♣0♦00
≤19	17	2168	128	500	Ø220	90123L00M0♣0♦00
≤19	24	3002	124	700	Ø220	90123L00H0♣0♦00

### DYNA

• To complete the product add the control gear. Please order separately.

## 02. Select options



### Product details

#### OPTIONS Code

##### Control gear HF

Driver 10,5W 10-42V 250mA HF	900002E
Driver 21W 10-42V 500MA HF	900007E
Driver 28W 28-40V 700MA HF	900303E

##### Control gear dimmable DALI

Driver 13W 09-52V 250mA DALI+ PUSH	900102H
Driver 26W 09-52V 500MA DALI+ PUSH	900107H
Driver 26,3W 09-37,5V 700mA DALI+ PUSH	900111H

##### Steel safety cable

L1500 mm	955000
----------	--------

##### Emergency unit (3 hours)

• Under request.



Heatsink



Front view