



Product characteristics


Body

Aluminium



Finish

Powder coated



Optical system

PB - Shiny reflector



Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

50.000h @ L90, B10, Ta 25°C




Control gear


LED driver 220-240V-50/60Hz included

01. Select version

ELI




PB - Shiny reflector - 35°



UGR	W	lm output	lm/W	CODE*
≤19	6	706	118	90671L200▼▲0◆35
≤19	9	1161	129	90564L200▼▲0◆35

PB - Shiny reflector - 60°



UGR	W	lm output	lm/W	CODE*
≤22	6	706	118	90671L200▼▲0◆60
≤22	9	1161	129	90564L200▼▲0◆60



*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour	
□ White	W
■ Black	B

Colour temp.	
3000K	3
4000K	0

ELI

• To complete the product add the current supply cable and the ceiling rose. Please order separately.

02. Select options



OPTIONS Code*

Transparent current supply cable

L1500 mm - 3 x 0,75 mm ²	940400
L1500 mm - 5 x 0,75 mm ²	940500
L3000 mm - 3 x 0,75 mm ²	940401
L3000 mm - 5 x 0,75 mm ²	940501
L6000 mm - 3 x 0,75 mm ²	940402
L6000 mm - 5 x 0,75 mm ²	940507

Round ceiling rose


Surface T24 D95	45  Ø95	978600▲
Recessed T5 D90	 Ø70 33  Ø90	971300▲

*Replace the symbols to complete the code

Colour	
□ White	W
■ Black	B



Product details



Ceiling rose