

FESAL



Product characteristics

Body

Aluminium

**Finish**

Powder coated

**Optical system**

PB - Shiny reflector

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

**LED lifetime**

50.000h @ L80, B10, Ta 25°C

Control gear

Not included


Ceiling thickness

For ceilings between 1-25 mm


01. Select version



FESAL



PB - Shiny reflector | Beam angle of 35°




UGR	W	lm output	lm/W	mA	Ø	CODE*
≤13	8	932	143	200	Ø132	90019L00L0▲0◆35
≤16	14	1578	134	350	Ø132	90019L00H0▲0◆35

*Replace the symbols to complete the code

Colour	Symbol
White	W
Black	B

Colour temp.	Symbol
3000K	B
4000K	A

PB - Shiny reflector | Beam angle of 60°



UGR	W	lm output	lm/W	mA	Ø	CODE*
≤19	8	953	146	200	Ø132	90019L00L0▲0◆60
≤19	14	1596	136	350	Ø132	90019L00H0▲0◆60

FESAL

• To complete the product add the control gear. Please order separately.

02. Select options

OPTIONS Code

Control gear HF

Driver 8,4W 10-42V 200mA HF	900001E
Driver 14,7W 10-42V 350mA HF	900004E

Control gear dimmable DALI

Driver 10,4W 09-52V 200mA DALI+ PUSH	900101H
Driver 18,2W 09-52V 350mA DALI+ PUSH	900104H

Steel safety cable

L1500 mm	955000
----------	--------