



### Product characteristics

---

**Body**  
Steel sheet

**Finish**  
White matte powder coated


**Optical system**  
DAM - Microprismatic diffuser  
LIGHT+ - Opal diffuser

**Light source**  
LED, RG1, CRI>80, MacAdam Step  $\leq 3$

**LED lifetime**  
80.000h @ L80, B10, Ta 25°C

**Control gear**  
LED driver 220-240V-50/60Hz included

---




## 01. Select version




### LNS

\*Replace the symbols to complete the code




#### DAM - Microprismatic diffuser



UGR	W	lm output	lm/W	LxWmm	CODE*
≤19	26	3169	122	873x320	90829L063▼W●◆00
≤19	34	4225	124	1149x320	90829L123▼W●◆00
≤19	42	5282	126	1425x320	90829L153▼W●◆00
≤19	34	4225	124	597x597	90829L066▼W●◆00

Control gear	
HF	E
DALI	H

#### LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	LxWmm	CODE*
≤22	26	3441	132	873x320	90830L063▼W●◆00
≤22	34	4587	135	1149x320	90830L123▼W●◆00
≤22	42	5734	137	1425x320	90830L153▼W●◆00
≤22	34	4587	135	597x597	90830L066▼W●◆00

Emergency	
No EM	0
EM 3h (K3) <sup>1</sup>	3

Colour temp.	
3000K	3
4000K	0

## 02. Select options



### Product details

#### OPTIONS

##### CRI>90

- Under request.



Frame with click system

<sup>1</sup> Prepared for emergency remote control.