



### Product characteristics


---

<b>Body</b>
Steel sheet
<b>Finish</b>
White matte powder coated
<b>Fixing system</b>
Pull-up: for plasterboard ceilings with brackets
<b>Optical system</b>
DCS - Microperforated diffuser
<b>Light source</b>
LED, RG1, CRI>80, MacAdam Step $\leq 3$
<b>LED lifetime</b>
80.000h @ L90, B10, Ta 25°C
<b>Control gear</b>
LED driver 220-240V-50/60Hz included
<b>Ceiling thickness</b>
For ceilings between 1-25 mm


---


## 01. Select version

TEI



### DCS - Microperforated diffuser



UGR	W	lm output	lm/W	□	CODE*
≤19	29	2223	77	578x578	90853L060▼W●◆♣
≤22	43	3334	78	578x578	90852L060▼W●◆♣



\*Replace the symbols to complete the code

Control gear	▼
HF	E
DALI	H

Emergency	●
No EM	0
EM 3h (K3) <sup>1</sup>	3

Colour temp.	◆
3000K	3
4000K	0

Connector	♣
No connector	00
W3M <sup>2</sup>	W3
W5MD <sup>3</sup>	W5

## 02. Select options

OPTIONS	Code
---------	------

<b>Steel safety cable</b> L1500 mm	955000
---------------------------------------	--------

### Bespoke projects

- Under request.

<sup>1</sup> Prepared for emergency remote control.

<sup>2</sup> 3-pole Wieland GST18i3 male connector.

<sup>3</sup> 5-pole Wieland GST18i5 DIM male connector.