





Product characteristics

Body Steel sheet
Finish White matte powder coated
Optical system DAZ - Opal diffuser
Light source LED, RG1, CRI>80, MacAdam Step ≤3
LED lifetime 80.000h @ L90, B10, Ta 25°C
Control gear LED driver 220-240V-50/60Hz included




01. Select version




*Replace the symbols to complete the code

TRN



DAZ - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
12	1747	146	590	90834L060▼W0♣♣
23	3494	146	1150	90834L120▼W0♣♣
29	4368	151	1430	90834L150▼W0♣♣

Control gear	
HF	E
DALI	H

Emergency	
No EM	0
EM 3h (K3) ¹	3

Colour temp.	
3000K	3
4000K	0

Connector	
No connector	00
M3M ²	M3
M5M ³	M5
M3MFC ⁴	C3
M5MFC ⁵	C5

Product details



Connector detail



LED

¹ Prepared for emergency remote control.

² 3-pole mini Wieland GST15i3 male connector.

³ 5-pole mini Wieland GST15i5 male connector.

⁴ 3-pole mini Wieland GST15i3 male connector + L1000 mm cable with 3-pole mini Wieland GST15i3 female connector.

⁵ 5-pole mini Wieland GST15i5 male connector + L1000 mm cable with 5-pole mini Wieland GST15i5 female connector.