

SENSE





SENSE

SENSE X



SENSE





Product characteristics

Body

Aluminium

Finish

Epoxy polyester powder coated

Optical system

DOZ - Opal polycarbonate diffuser

L1000 mm long H05-FVV supply cable

Light sourceLED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime 50.000h @ L80, B10, Ta 25°C

Control gear

Not included

Ceiling/Wall thickness

For plasterboard between 1-25 mm





230V/50Hz









O1. Select version

SENSE



DOZ - Opal polycarbonate diffuser



w	l ou
1	Ę
3	8

lm output	mA
50	350
84	700

 CODE*

 Ø46
 90062L101E♠0♦00

 Ø46
 90062L103E♠0♦00

*Replace the symbols to complete the code

olour	•
White	W
Black	В
	White

Colour temp.	•
3000K	3
4000K	(

SENSE

• To complete the product it is necessary to order the driver separately.

O2. Select options

OPTIONS	Code
HF driver	
Driver LED 350mA	965704
Driver LED 700mA	965705
IP20/65 version • Under request.	

SENSE X





Product characteristics

Body

Aluminium

Epoxy polyester powder coated

Optical system

DOZ - Opal polycarbonate diffuser

L1000 mm long H05-FVV supply cable

Light sourceLED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime 50.000h @ L80, B10, Ta 25°C

Control gear

Not included

InstallationFor concrete ceilings/walls





230V/50Hz











Select version

SENSE X





DOZ - Opai polycarb
90° 90° 90° 90° 90° 90° 90° 90° 90° 90°
C90 - C270 = =

olycarbonate diffuser		
90°	W 1 3	

	uuoo.	
w		l ou
1		(

Im output 50 84

mA 350 CODE* 90936L101E**♠**0♦00 90936L103E**♠**0♦00 700

*Replace the symbols to complete the code


♠ W Colour ☐ White ■ Black В

Colour temp. 3000K **♦** 4000K 0

SENSE X

• To complete the product it is necessary to order the recessing box and the driver. Please order separately.

Select options





Product details



Recessing box