

6th ELEMENT /C



Product characteristics

Body

Die-cast aluminium

**Finish**

Powder coated

**Optical system**

Lens

**Light source**

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

50.000h @ L80, B10, Ta 25°C

**Control gear**


Not included

01. Select version

6th ELEMENT /C




50° lens



UGR	W	lm output	lm/W	mA	CODE*
≤13	9	1128	125	250	90278L0090♣0♦50
≤13	12	1512	126	350	90278L0160♣0♦50

80° lens



UGR	W	lm output	lm/W	mA	CODE*
≤25	9	1091	121	250	90278L0090♣0♦80
≤25	12	1428	119	350	90278L0160♣0♦80



*Replace the symbols to complete the code

Colour	♣
□ White	W
■ Black	B
■ Rusty chain	R


Colour temp.	♦
3000K	B
4000K	A

6th ELEMENT /C

- To complete the product add ceiling rose. Please order separately.

02. Select ceiling rose

Recessed - T52 Q200



135x135

HF

	CODE*
10,5W 10-42V 250mA HF	972010♣
14,7W 10-42V 350mA HF	972011♣

DALI

	CODE*
13W 09-52V 250mA DALI	972020♣
18,2W 09-52V 350mA DALI	972021♣

Surface mounted - T51 D120



HF

	CODE*
10W 30-42V 250mA HF	972030♣
15W 26-43V 350mA HF	972031♣

DALI

	CODE*
12W 03-45V 250mA DALI	972040♣
16W 03-45V 350mA DALI	972041♣



*Replace the symbols to complete the code

Colour	♣
□ White	W
■ Black	B
■ Rusty chain	R

CEILING ROSE

- The recessed ceiling rose T52 Q200 is class II.
- The surface ceiling rose T51 D120 is class I.
- Control gear included in the ceiling rose.



Select options



Light effect with
50° lens



Light effect with
80° lens



Ceiling roses

