

6th ELEMENT FIX



Product characteristics

Body

Die-cast aluminium



Finish

Powder coated



Optical system

Lens

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3



LED lifetime

50.000h @ L80, B10, Ta 25°C

Control gear

Not included

Ceiling thickness

For ceilings between 10-25mm


01. Select version



6th ELEMENT FIX




50° lens



UGR	W	lm output	lm/W	mA	Φ	CODE*
≤13	9	1128	125	250	Ø125	90303L0090▲0◆50
≤13	12	1512	126	350	Ø125	90303L0160▲0◆50

80° lens



UGR	W	lm output	lm/W	mA	Φ	CODE*
≤25	9	1091	121	250	Ø125	90303L0090▲0◆80
≤25	12	1428	119	350	Ø125	90303L0160▲0◆80

*Replace the symbols to complete the code

Colour	Symbol
White	W
Black	B
Rusty chain	R

Colour temp.	Symbol
3000K	B
4000K	A

6th ELEMENT FIX

• To complete the product add control gear. Please order separately.

02. Select options



Select options

OPTIONS Code

Control gear HF

Driver 10,5W 10-42V 250mA HF	900002E
Driver 14,7W 10-42V 350mA HF	900004E

Control gear dimmable DALI

Driver 13W 09-52V 250mA DALI+ PUSH	900102H
Driver 18,2W 09-52V 350mA DALI+ PUSH	900104H

Steel safety cable

L1500 mm	955000
----------	--------



Light effect with 50° lens



Light effect with 80° lens