

## 6th ELEMENT +



### Product characteristics

---

**Body**

Die-cast aluminium

**Finish**

Powder coated

**Optical system**

Lens

**Light source**

LED, RG1, CRI>90, MacAdam Step  $\leq 3$

**LED lifetime**

50.000h @ L80, B10, Ta 25°C

**Control gear**

Not included


---




01. Select version



6th ELEMENT +




50° lens | Direct / Indirect (50%/50%)




UGR	W	lm output	lm/W	mA	CODE*
≤10	17	2232	131	500	90568L0160▲0◆50

80° lens | Direct / Indirect (50%/50%)




UGR	W	lm output	lm/W	mA	CODE*
≤19	17	2158	127	500	90568L0160▲0◆80

50° lens | Direct



UGR	W	lm output	lm/W	mA	CODE*
≤13	9	1128	125	250	90578L0090▲0◆50
≤13	12	1512	126	350	90578L0160▲0◆50

80° lens | Direct



UGR	W	lm output	lm/W	mA	CODE*
≤25	9	1091	121	250	90578L0090▲0◆80
≤25	12	1428	119	350	90578L0160▲0◆80

\*Replace the symbols to complete the code

Colour	Symbol
White	W
Black	B
Rusty chain	R


Colour temp.	Symbol
3000K	B
4000K	A

6th ELEMENT +

• To complete the product add current supply cable/suspension and ceiling rose. Please order separately.

## 02. Select ceiling rose

### Recessed - T55 Q200



135x135

#### HF

	CODE*
10,5W 10-42V 250mA HF	972710♣
14,7W 10-42V 350mA HF	972711♣
21W 10-42V 500mA HF	972712♣

#### DALI

	CODE*
13W 09-52V 250mA DALI	972720♣
18,2W 09-52V 350mA DALI	972721♣
26W 09-52V 500mA DALI	972722♣

### Surface mounted - T54 D120



#### HF

	CODE*
10W 30-42V 250mA HF	972730♣
15W 26-43V 350mA HF	972731♣
21W 30-42V 500mA HF	972732♣

#### DALI

	CODE*
12W 03-45V 250mA DALI	972740♣
16W 03-45V 350mA DALI	972741♣
20W 03-40V 500mA DALI	972742♣

#### CEILING ROSE

- The recessed ceiling rose T55 Q200 is class II.
- The surface ceiling rose T54 D120 is class I.
- Control gear included in the ceiling rose.

## 03. Select options

### OPTIONS Code

#### Current supply cable / Suspension

L1500 mm (x3)	942900
L3000 mm (x3)	942901
L6000 mm (x3)	942902



\*Replace the symbols to complete the code

Colour	♣
□ White	W
■ Black	B
■ Rusty chain	R




### Select options



Light effect with 50° lens



Light effect with 80° lens



Ceiling roses

