

6th ELEMENT /W



Product characteristics

Body

Die-cast aluminium



Finish

Powder coated



Optical system

Lens



Light source

LED, RG1, CRI>90, MacAdam Step ≤3

LED lifetime

50.000h @ L80, B10, Ta 25°C


Control gear

Not included


01. Select version



6th ELEMENT /W




50° lens | Direct / Indirect (50%/50%)



UGR	W	lm output	lm/W	mA	CODE*
≤10	17	2232	131	500	90279L0160▲0◆50

CO - C180 —
C90 - C270 - -


80° lens | Direct / Indirect (50%/50%)



UGR	W	lm output	lm/W	mA	CODE*
≤19	17	2158	127	500	90279L0160▲0◆80

CO - C180 —
C90 - C270 - -


50° lens | Direct



UGR	W	lm output	lm/W	mA	CODE*
≤13	9	1128	125	250	90330L0090▲0◆50
≤13	12	1512	126	350	90330L0160▲0◆50

CO - C180 —
C90 - C270 - -

80° lens | Direct



UGR	W	lm output	lm/W	mA	CODE*
≤25	9	1091	121	250	90330L0090▲0◆80
≤25	12	1428	119	350	90330L0160▲0◆80

CO - C180 —
C90 - C270 - -

*Replace the symbols to complete the code

Colour	◆
□ White	W
■ Black	B
■ Rusty chain	R


Colour temp.	◆
3000K	B
4000K	A

6th ELEMENT /W

- To complete the product add ceiling rose. Please order separately.

02. Select ceiling rose

Recessed - T52 Q200




HF

	CODE*
10,5W 10-42V 250mA HF	972010♣
14,7W 10-42V 350mA HF	972011♣
21W 10-42V 500mA HF	972012♣

DALI

	CODE*
13W 09-52V 250mA DALI	972020♣
18,2W 09-52V 350mA DALI	972021♣
26W 09-52V 500mA DALI	972022♣

Surface mounted - T51 D120



HF

	CODE*
10W 30-42V 250mA HF	972030♣
15W 26-43V 350mA HF	972031♣
21W 30-42V 500mA HF	972032♣

DALI

	CODE*
12W 03-45V 250mA DALI	972040♣
16W 03-45V 350mA DALI	972041♣
20W 03-40V 500mA DALI	972042♣



*Replace the symbols to complete the code

Colour	♣
□ White	W
■ Black	B
■ Rusty chain	R

CEILING ROSE

- The recessed ceiling rose T52 Q200 is class II.
- The surface ceiling rose T51 D120 is class I.
- Control gear included in the ceiling rose.



Select options



Light effect with
50° lens



Light effect with
80° lens



Surface mounted
ceiling rose

