



Product characteristics


Body

Steel sheet



Frame

Aluminium



Finish

White matte powder coated



Fixing system

Lay-in: for exposed T grid ceilings without brackets



Wiring

Pre-wired with 1000 mm long H05VV-F cable

Optical system

DAM - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L80, B10, Ta 25°C

Control gear


LED driver 220-240V-50/60Hz included

01. Select version




AVT

*Replace the symbols to complete the code




DAM - Microprismatic diffuser



UGR	W	lm output	lm/W	LxWmm	L1xW1mm	CODE*
≤19	34	4104	121	1197x297	1175x275	90797L123▼W●000
≤19	42	5131	122	1497x297	1475x275	90797L153▼W●000
≤22	74	8656	117	1497x297	1475x275	90799L153▼W●000
≤19	34	4104	121	597x597	575x575	90797L066▼W●000
≤19	59	6925	117	597x597	575x575	90799L066▼W●000

LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	LxWmm	L1xW1mm	CODE*
≤22	34	4527	133	1197x297	1175x275	90798L123▼W●000
≤22	42	5659	135	1497x297	1475x275	90798L153▼W●000
≤25	74	9548	129	1497x297	1475x275	90800L153▼W●000
≤22	34	4527	133	597x597	575x575	90798L066▼W●000
≤22	59	7638	129	597x597	575x575	90800L066▼W●000

Control gear

HF	E
DALI	H

Emergency

No EM	0
EM 3h (K3) ¹	3

02. Select options



Product details

OPTIONS Code

Connector	Code
3-pole Wieland GST18i3 male connector	965301
5-pole Wieland GST18i5 DIM male connector	965403


Steel safety cable	Code
L1500 mm	955000

CRI>90

- Under request.

Bespoke projects

- Under request.



Lay-in recessed version

¹ Prepared for emergency remote control.