

CIRION Line



Product characteristics

Body

Extruded aluminium profile

Finish

Epoxy polyester powder coated

Optical system

bOPTICS - Symmetric reflector

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime

80.000h @ L80, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz




IP 40

bOPTICS
650°C


01. Select version



CIRION Line



bOPTICS - Symmetric reflector



UGR	W	lm output	lm/W	Lmm	CODE*
<19	21	2930	140	840	90893L003♥♣0♦00
<19	27	3906	145	1120	90893L004♥♣0♦00
<19	34	4883	144	1400	90893L005♥♣0♦00
<19	40	5859	146	1680	90893L006♥♣0♦00
<19	48	6836	142	1960	90893L007♥♣0♦00
<19	54	7812	145	2240	90893L008♥♣0♦00
<19	61	8712	144	2520	90893L009♥♣0♦00
<19	68	9765	144	2800	90893L010♥♣0♦00

*Replace the symbols to complete the code

Control gear	♥
HF	E
DALI	H

Colour	♣
□ White	W
■ Black	B

Emergency	●
No EM	0
EM 3h (K3)	3

Colour temp.	♦
3000K	3
4000K	0

CIRION Line

- The values indicated refer to the colour white.
- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.
- To complete the product it is necessary to order the start kit, through-wiring and body connector kit. Please order separately.
- Dimensions do not include start kit. To complete the line add 6 mm to the length.
- The maximum line length with 1 single feed/power point is 30000 mm.

02. Select options

OPTIONS	Code*
Start kit - end cap start/end	924200▲
• 2 end caps included.	
Suspension	
S24 L1500mm (x1)	9139001
S24 L3000mm (x1)	9139002
S24 L6000mm (x1)	9139003
• For length L2800 mm, order 1 suspension (central).	
• For the open-line version, order 2 suspensions (start and end) plus 1 additional suspension for each body connector kit.	
• For the closed-line version, order 1 suspension for each body connector kit.	
Through-wiring	
• Standard	
3 x 1,5 mm ²	940300
3 x 1,5 mm ² L0600	945652
5 x 1,5 mm ²	940301
5 x 1,5 mm ² L0600	945752
• 2 x 1,5 mm²	
HF+K3 (x1)	948000
HF+K3 (x1) L3100	948010
• 2 x 1,5 mm² + 5P junction	
DALI+K3 (x1)	948200
DALI+K3 (x1) L3100	948210
• 2 x 1,5 mm² + 2 x 0,75 mm² and 5P junction	
K3+TEL (x1)	948100
K3+TEL (x1) L3100	948210
Body connector kit (x1)	932400
• Screws included.	
Body connector kit 90° (x1)	932401
• Screws included.	
• To complete the 90° body connector kit, it is necessary to order the L0600 through-wiring.	
Current supply cable	
L1500mm - 3 x 1,5 mm ²	940300
L1500mm - 5 x 1,5 mm ²	940000
L1500mm - 7 x 1,5 mm ²	940100
L3000mm - 3 x 1,5 mm ²	940301
L3000mm - 5 x 1,5 mm ²	940001
L3000mm - 7 x 1,5 mm ²	940101
L6000mm - 3 x 1,5 mm ²	940302
L6000mm - 5 x 1,5 mm ²	940002
L6000mm - 7 x 1,5 mm ²	940102
• For the option DALI with emergency unit and remote control, it is necessary to order 2 current supply cables of 5 x 1,5 mm ² .	
Ceiling rose	
Surface mounted T64 35  Ø85	979000▲
Surface mounted T69 (DALI+K3)	979003▲
Recessed T5  Ø70 33  Ø90	971300▲
Recessed T27 (DALI+K3)	979700▲



*Replace the symbols to complete the code

Colour	▲
☐ White	W
☒ Black	B



Product details




End caps without visible screws



Body connector without light leakage




Suspended application




bOPTICS diffuser



Body connector kit 90°



Start kit



Ceiling rose

