

CONCEPT O 35 D/I



Product characteristics

Body

Aluminium



Finish

Powder coated

230V/50Hz

Optical system

bFLEX - Opal diffuser



IP 40

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime

70.000h @ L90, B10, Ta 25°C



Control gear

LED driver 220-240V-50/60Hz included


01. Select version



CONCEPT O 35 D/I



bFLEX - Opal diffuser (80%/20%)



W	lm output	lm/W	Dmm	CODE*
83	8253	99	Ø777	90540L016▼▲◆0◆00
128	12380	97	Ø1136	90540L024▼▲◆0◆00
166	16506	99	Ø1494	90540L032▼▲◆0◆00
220	20633	94	Ø1853	90540L040▼▲◆0◆00
304	29711	98	Ø2569	90540L056▼▲◆0◆00
332	33012	99	Ø2926	90540L064▼▲◆0◆00
488	46217	95	Ø4000	90540L088▼▲◆0◆00
664	66024	99	Ø5789	90540L128▼▲◆0◆00
976	92434	95	Ø7936	90540L176▼▲◆0◆00

*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour ¹	
White	W
Gray	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D
Old rose	5
Copper	7

CONCEPT O 35 D/I

- To complete the product add current supply cable, suspension and ceiling rose. Please order separately.
- For all diameters above Ø1494 mm the product is composed by multiple modules.
- In order to guarantee a total uniformity of light on the ceiling, the installation must be done at a minimum distance of 500 mm.
- Create your own configurations on CONFIGURATOR.INDELAGEGROUP.COM.

Colour temp.	
3000K	3
4000K	0

¹ See page 84.

02. Select options

OPTIONS	Code*
SwitchDIM	
• Under request.	
Suspension	
S11 (x3) - Ø777 mm	912903▲
S11 (x4) - Ø1136 mm	912904▲
S11 (x6) - Ø1494, Ø1853 mm	912906▲
S11 (x8) - Ø2569 mm	912908▲
S11 (x12) - Ø2926, Ø4000 mm	912912▲
S11 (x24) - Ø5789 mm	912924▲
S11 (x32) - Ø7936 mm	912932▲
Transparent current supply cable	
L1500 mm - 3 x 0,75 mm ²	940400
L1500 mm - 5 x 0,75 mm ²	940500
L3000 mm - 3 x 0,75 mm ²	940401
L3000 mm - 5 x 0,75 mm ²	940501
L6000 mm - 3 x 0,75 mm ²	940402
L6000 mm - 5 x 0,75 mm ²	940507
Round ceiling rose	
Surface mounted T24 D95  45  Ø95	978600▲
Recessed T5 D90  Ø70 33  Ø90	971300▲
Central ceiling rose	
Surface mounted T20 3I - Ø777 mm	977201▲
Surface mounted T20 4I - Ø1136 mm	977202▲
Surface mounted T20 6I - Ø1494 mm	977204▲
 45  Ø95	
Acoustic moss	
Ø777 mm	926801
Ø1136 mm	926802
• Sound absorption and humidity control.	
• Other diameters available under request.	
Acoustic panel	
Ø777 mm	926901
Ø1136 mm	926902
• Sound absorption.	
• Other diameters available under request.	



*Replace the symbols to complete the code

Length	▲
L1500 mm	1
L3000 mm	2
L6000 mm	3

Colour	▲
<input type="checkbox"/> White	W
<input checked="" type="checkbox"/> Black	B



Select options



Indirect light



bFLEX diffuser



Acoustic moss




Acoustic moss (macro)



Acoustic panel



Acoustic panel (macro)



Ceiling roses

