

CONCEPT O 65 D/I



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

gCONTROL+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz




IP 20

650°C


01. Select version



CONCEPT O 65 D/I




gCONTROL+ - Microprismatic diffuser (80%/20%)



UGR	W	lm output	lm/W	Dmm	CODE*
≤19	44	4580	104	Ø600	90626L600▼▲◆0◆00
≤19	63	6651	106	Ø900	90626L900▼▲◆◆◆00
≤19	92	9596	104	Ø1200	90626L120▼▲◆◆◆00
≤19	110	11558	105	Ø1500	90626L150▼▲◆◆◆00

LIGHT+ - Opal diffuser (80%/20%)



UGR	W	lm output	lm/W	Dmm	CODE*
≤22	44	4817	109	Ø600	90636L600▼▲◆0◆00
≤22	63	6995	111	Ø900	90636L900▼▲◆◆◆00
≤22	92	10092	110	Ø1200	90636L120▼▲◆◆◆00
≤22	110	12156	111	Ø1500	90636L150▼▲◆◆◆00

*Replace the symbols to complete the code

Control gear

HF	E
DALI	H

Colour¹

White	W
Gray	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D
Old rose	5
Copper	7

CONCEPT O 65

- To complete the product add current supply cable, suspension and ceiling rose. Please order separately.
- In order to guarantee a total uniformity of light on the ceiling, the installation must be done at a minimum distance of 500 mm.

Emergency

No EM	0
EM 3h (K3) ²	3

Colour temp.

3000K	3
4000K	0

¹ See page 136.

² Prepared for emergency remote control.

02. Select options

OPTIONS	Code*
Bluetooth • Bluetooth wireless control via smartphone.	927200
Suspension S10 L1500 mm (x3) S10 L3000 mm (x3) S10 L6000 mm (x3)	9111001 9111002 9111003
Transparent current supply cable L1500 mm - 3 x 0,75 mm ² L1500 mm - 5 x 0,75 mm ² L1500 mm - 7 x 0,75 mm ² L3000 mm - 3 x 0,75 mm ² L3000 mm - 5 x 0,75 mm ² L3000 mm - 7 x 0,75 mm ² L6000 mm - 3 x 0,75 mm ² L6000 mm - 5 x 0,75 mm ² L6000 mm - 7 x 0,75 mm ² • For the DALI option with emergency unit and remote control add 2 current supply cables of 5 x 0,75 mm ² .	940400 940500 940600 940401 940501 940601 940402 940507 940602
Round ceiling rose Surface mounted T24 D95 45 l  Ø95 Surface mounted T26 D95 (DALI+K3)	978600♣ 978601♣
Recessed T5 D90  Ø70 33 l  Ø90 Recessed T27 D90 (DALI+K3)	971300♣ 978700♣
Central ceiling rose Surface T21 3l D95 45 l  Ø95 Surface T28 3l D95 (DALI+K3)	977211♣ 977230♣



*Replace the symbols to complete the code

Colour 
 White W
 Black B



Select options



Suspended application



Suspended application with central ceiling rose



gCONTROL+ diffuser



LIGHT+ diffuser



Indirect light



Parallel suspension with recessed ceiling rose



Parallel suspension with surface mounted ceiling rose



Central suspension

