

## CONCEPT O 65



### Product characteristics

**Body**

Aluminium

**Finish**

Powder coated

**Optical system**

gCONTROL+ - Microprismatic diffuser  
LIGHT+ - Opal diffuser

**Light source**

LED, RG1, CRI>80, MacAdam Step  $\leq 3$

**LED lifetime**

80.000h @ L90, B10, Ta 25°C

**Control gear**

LED driver 220-240V-50/60Hz included



230V/50Hz




IP 20


650°C

01. Select version

CONCEPT O 65




gCONTROL+ - Microprismatic diffuser



UGR	W	lm output	lm/W	Dmm	CODE*
≤19	38	3722	98	Ø600	90625L600▼▲◆0◆00
≤19	54	5377	100	Ø900	90625L900▼▲◆◆◆00
≤19	77	7858	102	Ø1200	90625L120▼▲◆◆◆00
≤19	91	9099	100	Ø1500	90625L150▼▲◆◆◆00

LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	Dmm	CODE*
≤22	38	3993	105	Ø600	90635L600▼▲◆0◆00
≤22	54	5768	107	Ø900	90635L900▼▲◆◆◆00
≤22	77	8430	109	Ø1200	90635L120▼▲◆◆◆00
≤22	91	9761	107	Ø1500	90635L150▼▲◆◆◆00

CONCEPT O 65

• For suspended version add current supply cable, suspension and ceiling rose. Please order separately.



\*Replace the symbols to complete the code

**Control gear**

HF	E
DALI	H

**Colour<sup>1</sup>**

White	W
Gray	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D
Old rose	5
Copper	7

**Emergency**

No EM	0
EM 3h (K3) <sup>2</sup>	3

**Colour temp.**

3000K	3
4000K	0

<sup>1</sup> See page 136.

<sup>2</sup> Prepared for emergency remote control.

## 02. Select options

OPTIONS	Code*
<b>Bluetooth</b> • Bluetooth wireless control via smartphone.	927200
<b>Suspension</b> S10 L1500 mm (x3) S10 L3000 mm (x3) S10 L6000 mm (x3)	9111001 9111002 9111003
<b>Transparent current supply cable</b> L1500 mm - 3 x 0,75 mm <sup>2</sup> L1500 mm - 5 x 0,75 mm <sup>2</sup> L1500 mm - 7 x 0,75 mm <sup>2</sup> L3000 mm - 3 x 0,75 mm <sup>2</sup> L3000 mm - 5 x 0,75 mm <sup>2</sup> L3000 mm - 7 x 0,75 mm <sup>2</sup> L6000 mm - 3 x 0,75 mm <sup>2</sup> L6000 mm - 5 x 0,75 mm <sup>2</sup> L6000 mm - 7 x 0,75 mm <sup>2</sup> • For the DALI option with emergency unit and remote control, add 2 current supply cables of 5 x 0,75 mm <sup>2</sup> .	940400 940500 940600 940401 940501 940601 940402 940507 940602
<b>Round ceiling rose</b> Surface mounted T24 D95 45 l  Ø95 Surface mounted T26 D95 (DALI+K3) 	978600♣ 978601♣
Recessed T5 D90  Ø70 33 l  Ø90 Recessed T27 D90 (DALI+K3) 	971300♣ 978700♣
<b>Central ceiling rose</b> Surface T21 3l D95 45 l  Ø95 Surface T28 3l D95 (DALI+K3) 	977211♣ 977230♣



\*Replace the symbols to complete the code

**Colour**   
 White W  
 Black B



## Select options



Ceiling surface application



Suspended application



Suspended application with central ceiling rose



Wall application



gCONTROL+ diffuser



LIGHT+ diffuser



Parallel suspension with recessed ceiling rose



Parallel suspension with surface mounted ceiling rose



Central suspension

