

## CONCEPT S 35 D/I



### Product characteristics

#### Body

Aluminium



#### Finish

Powder coated

230V/50Hz

#### Optical system

bFLEX - Opal diffuser not included

#### Wiring

Through-wiring included



IP 40

#### Light source

LED, RG1, CRI>80, MacAdam Step  $\leq 3$



#### LED lifetime

70.000h @ L90, B10, Ta 25°C

#### Control gear

LED driver 220-240V-50/60Hz included


# 01. Select module




## CURVED MODULE




### 1/16 (22,5°) | bFLEX - Opal diffuser (Not included) (80%/20%)




W	lm output	lm/W	Lmm	Dmm	CODE*
61	5777	95	1548	Ø7936	90547▲011▼▲0♣♣




### 1/8 (45°) | bFLEX - Opal diffuser (Not included) (80%/20%)




W	lm output	lm/W	Lmm	Dmm	CODE*
44	4127	94	1120	Ø2926	90548▲008▼▲0♣♣
61	5777	95	1531	Ø4000	90548▲011▼▲0♣♣
83	8253	99	2215	Ø5789	90548▲016▼▲0♣♣




### 1/4 (90°) | bFLEX - Opal diffuser (Not included) (80%/20%)



W	lm output	lm/W	Lmm	Dmm	CODE*
44	4127	94	1057	Ø1494	90549▲008▼▲0♣♣
57	5364	94	1310	Ø1853	90549▲010▼▲0♣♣
76	7428	98	1816	Ø2568	90549▲014▼▲0♣♣
83	8253	99	2069	Ø2926	90549▲016▼▲0♣♣
122	11554	95	2828	Ø4000	90549▲022▼▲0♣♣



### 1/2 (180°) | bFLEX - Opal diffuser (Not included) (80%/20%)



W	lm output	lm/W	Lmm	Dmm	CODE*
44	4127	94	777	Ø777	90550▲008▼▲0♣♣
64	6190	97	1136	Ø1136	90550▲012▼▲0♣♣
83	8253	99	1494	Ø1494	90550▲016▼▲0♣♣
110	10316	94	1853	Ø1853	90550▲020▼▲0♣♣

\*Replace the symbols to complete the code

Module direction ▲  
LEFT L  
RIGHT R

Control gear ▼  
HF E  
DALI H

Colour 1 ♣  
□ White W  
■ Gray G  
■ Black B  
■ Sahara 0  
■ Mist 1  
■ Carbon I  
■ Autumn L  
■ Rusty chain R  
■ Jungle N  
■ Golden eye D  
■ Old rose 5  
■ Copper 7


Colour temp. ♦  
3000K 3  
4000K 0

Module ♣  
SRT 49  
MID/END 98

## LINEAR MODULE



### LINEA | bFLEX - Opal diffuser (Not included) (80%/20%)



W	lm output	lm/W	Lmm	CODE*
44	4127	94	1124	90542L008▼▲0♣♣
57	5364	94	1405	90542L010▼▲0♣♣
64	6190	97	1686	90542L012▼▲0♣♣
76	7428	98	1967	90542L014▼▲0♣♣
83	8253	99	2248	90542L016▼▲0♣♣
94	9491	101	2529	90542L018▼▲0♣♣
110	10316	94	2810	90542L020▼▲0♣♣

## CURVED MODULE | LINEAR MODULE

- To complete the individual product add bFLEX diffuser, start kit, current supply cable, suspension and ceiling rose. Please order separately.
- To complete the line add bFLEX diffuser, current supply cable, suspensions, start kit and body connector kit. Please order separately.
- Dimensions do not include the start kit. Add 26 mm to the recessing length to complete the line.
- In order to guarantee a total uniformity of light on the ceiling, the installation must be done at a minimum distance of 500 mm.
- Create your own configurations on CONFIGURATOR.INDELAGEGROUPE.COM.

## 02. Select options

OPTIONS	Code*
<b>BFLEX diffuser</b>	
L5000 mm	985705
L15000 mm	985715
L30000 mm	985730
<b>SwitchDIM</b>	
• Under request.	
<b>Start kit - end cap start/end</b>	
• 2 end caps included.	55   923000♣ 56   13   35
<b>Body connector (x1)</b>	
• Screws included.	932000
<b>Suspension</b>	
• For all curved versions and linea versions of L1967, L2248, L2529, L2810 mm:	
S11 L1500 mm (x3)	9129031
S11 L3000 mm (x3)	9129032
S11 L6000 mm (x3)	9129033
• For Linea versions of L843, L1124, L1405, L1686 mm:	
S11 L1500 mm (x2)	9129021
S11 L3000 mm (x2)	9129022
S11 L6000 mm (x2)	9129023
<b>Transparent current supply cable</b>	
L1500 mm - 3 x 1,5 mm <sup>2</sup>	940300
L1500 mm - 5 x 1,5 mm <sup>2</sup>	940000
L3000 mm - 3 x 1,5 mm <sup>2</sup>	940301
L3000 mm - 5 x 1,5 mm <sup>2</sup>	940001
L6000 mm - 3 x 1,5 mm <sup>2</sup>	940302
L6000 mm - 5 x 1,5 mm <sup>2</sup>	940002
<b>Round ceiling rose<sup>1</sup></b>	
Surface mounted T24 D95 45    Ø95	978600♣
Recessed T5 D90  Ø70 33    Ø90	971300♣
<b>Ceiling marking kit</b>	
• Under request.	



\*Replace the symbols to complete the code

Colour <sup>1 2</sup>	♣
<input type="checkbox"/> White	W
<input type="checkbox"/> Gray	G
<input type="checkbox"/> Black	B
<input type="checkbox"/> Sahara	0
<input type="checkbox"/> Mist	1
<input type="checkbox"/> Carbon	I
<input type="checkbox"/> Autumn	L
<input type="checkbox"/> Rusty chain	R
<input type="checkbox"/> Jungle	N
<input type="checkbox"/> Golden eye	D
<input type="checkbox"/> Old rose	5
<input type="checkbox"/> Copper	7



## Select options



End caps without visible screws



Suspended application



Fast connection



Continuous diffuser



Indirect light



bFLEX diffuser




Diffuser detail



Start kit



Body connector



Ceiling roses

<sup>1</sup>The ceiling roses are only available in White or Black colour.

<sup>2</sup> See page 84.

