

CONCEPT S 35



Product characteristics

Body

Aluminium



Finish

Powder coated

230V/50Hz

Optical system

bFLEX - Opal diffuser not included



IP 40

Wiring

Through-wiring included

Light source

LED, RG1, CRI>80, MacAdam Step ≤3



LED lifetime

70.000h @ L90, B10, Ta 25°C


Control gear

LED driver 220-240V-50/60Hz included


01. Select module




CURVED MODULE




1/16 (22,5°) | bFLEX - Opal diffuser (Not included)



W	Im output	Im/W	Lmm	Dmm	CODE*
49	4539	93	1548	Ø7936	90543▲011▼▲0♣♣




1/8 (45°) | bFLEX - Opal diffuser (Not included)




W	Im output	Im/W	Lmm	Dmm	CODE*
24	2063	86	709	Ø1853	90544▲005▼▲0♣♣
32	2889	90	983	Ø2569	90544▲007▼▲0♣♣
36	3301	92	1120	Ø2926	90544▲008▼▲0♣♣
49	4539	93	1531	Ø4000	90544▲011▼▲0♣♣
68	6602	97	2215	Ø5789	90544▲016▼▲0♣♣




1/4 (90°) | bFLEX - Opal diffuser (Not included)



W	Im output	Im/W	Lmm	Dmm	CODE*
28	2476	88	803	Ø1136	90545▲006▼▲0♣♣
36	3301	92	1057	Ø1494	90545▲008▼▲0♣♣
44	4127	94	1310	Ø1853	90545▲010▼▲0♣♣
61	5777	95	1816	Ø2569	90545▲014▼▲0♣♣
68	6602	97	2069	Ø2926	90545▲016▼▲0♣♣
90	9078	101	2828	Ø4000	90545▲022▼▲0♣♣



1/2 (180°) | bFLEX - Opal diffuser (Not included)



W	Im output	Im/W	Lmm	Dmm	CODE*
36	3301	92	777	Ø777	90546▲008▼▲0♣♣
53	4952	93	1136	Ø1136	90546▲012▼▲0♣♣
68	6602	97	1494	Ø1494	90546▲016▼▲0♣♣
83	8253	99	1853	Ø1853	90546▲020▼▲0♣♣

*Replace the symbols to complete the code

Module direction ▲
LEFT L
RIGHT R


Control gear ▼
HF E
DALI H

Colour ¹ ♣
□ White W
■ Gray G
■ Black B
■ Sahara 0
■ Mist 1
■ Carbon I
■ Autumn L
■ Rusty chain R
■ Jungle N
■ Golden eye D
■ Old rose 5
■ Copper 7


Colour temp. ♦
3000K 3
4000K 0

Module ♣
SRT 49
MID/END 98

LINEAR MODULE



LINEA | bFLEX - Opal diffuser (Not included)



W	Im output	Im/W	Lmm	CODE*
28	2476	88	843	90541L006▼▲0♣♣
36	3301	92	1124	90541L008▼▲0♣♣
44	4127	94	1405	90541L010▼▲0♣♣
53	4952	93	1686	90541L012▼▲0♣♣
61	5777	95	1967	90541L014▼▲0♣♣
68	6602	97	2248	90541L016▼▲0♣♣
76	7428	98	2529	90541L018▼▲0♣♣
83	8253	99	2810	90541L020▼▲0♣♣

CURVED MODULE | LINEAR MODULE

- To complete the individual product add bFLEX diffuser and start kit. Please order separately.
- To complete the line add bFLEX diffuser, start kit and body connector kit. Please order separately.
- For suspended version add current supply cable, suspension and ceiling rose. Please order separately.
- Dimensions do not include the start kit. Add 26 mm to the recessing length to complete the line.
- Create your own configurations on CONFIGURATOR.INDELAGUEGROUP.COM.

02. Select options

OPTIONS	Code*
BFLEX diffuser	
L5000 mm	985705
L15000 mm	985715
L30000 mm	985730
SwitchDIM	
• Under request.	
Start kit - end cap start/end	923000♣
• 2 end caps included.	
Body connector (x1)	932000
• Screws included.	
Suspension	
• For all curved versions and linea versions of L1967, L2248, L2529, L2810 mm:	
S11 L1500 mm (x3)	9129031
S11 L3000 mm (x3)	9129032
S11 L6000 mm (x3)	9129033
• For Linea versions of L843, L1124, L1405, L1686 mm:	
S11 L1500 mm (x2)	9129021
S11 L3000 mm (x2)	9129022
S11 L6000 mm (x2)	9129023
Transparent current supply cable	
L1500 mm - 3 x 1,5 mm ²	940300
L1500 mm - 5 x 1,5 mm ²	940000
L3000 mm - 3 x 1,5 mm ²	940301
L3000 mm - 5 x 1,5 mm ²	940001
L6000 mm - 3 x 1,5 mm ²	940302
L6000 mm - 5 x 1,5 mm ²	940002
Round ceiling rose ¹	
Surface mounted T24 D95 45 Ø95	978600♣
Recessed T5 D90 Ø70 33 Ø90	971300♣
Ceiling marking kit	
• Under request.	



*Replace the symbols to complete the code

Colour ¹²	♣
<input type="checkbox"/> White	W
<input type="checkbox"/> Gray	G
<input type="checkbox"/> Black	B
<input type="checkbox"/> Sahara	0
<input type="checkbox"/> Mist	1
<input type="checkbox"/> Carbon	I
<input type="checkbox"/> Autumn	L
<input type="checkbox"/> Rusty chain	R
<input type="checkbox"/> Jungle	N
<input type="checkbox"/> Golden eye	D
<input type="checkbox"/> Old rose	5
<input type="checkbox"/> Copper	7



Select options



End caps without visible screws



Ceiling surface application



Suspended application



Fast connection



Continuous diffuser



bFLEX diffuser



Diffuser detail



Start kit



Body connector



Ceiling roses

