

CONCEPT Sq 35



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

bFLEX - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime

70.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz



IP 40




01. Select version

CONCEPT Sq 35



bFLEX - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
112	10450	93	1126	90704L027▼▲0◆00
140	13752	98	1441	90704L033▼▲0◆00

CONCEPT Sq 35

• For suspended version add current supply cable, suspension and ceiling rose. Please order separately.



*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour ¹	
White	W
Gray	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D
Old rose	5
Copper	7

Colour temp.	
3000K	3
4000K	0

¹ See page 84.

02. Select options

OPTIONS	Code*
SwitchDIM	
• Under request.	
Suspension	
S11 L1500 mm (x4)	9129041
S11 L3000 mm (x4)	9129042
S11 L6000 mm (x4)	9129043
Transparent current supply cable	
L1500 mm - 3 x 0,75 mm ²	940400
L1500 mm - 5 x 0,75 mm ²	940500
L3000 mm - 3 x 0,75 mm ²	940401
L3000 mm - 5 x 0,75 mm ²	940501
L6000 mm - 3 x 0,75 mm ²	940402
L6000 mm - 5 x 0,75 mm ²	940507
Round ceiling rose	
Surface mounted T24 D95 45 l  Ø95	978600▲
Recessed T5 D90  Ø70 33 l  Ø90	971300▲
Central ceiling rose	
Surface mounted T20 4l 45 l  Ø95	977202▲



*Replace the symbols to complete the code

Colour	▲
<input type="checkbox"/> White	W
<input checked="" type="checkbox"/> Black	B



Select options



bFLEX diffuser



Ceiling roses

