

CORA /C



Product characteristics

Body

Steel sheet



Finish

Powder coated

230V/50Hz

Optical system

bOPTICS - Symmetric reflector

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3



IP 20

LED lifetime

80.000h @ L90, B10, Ta 25°C

650°C


Control gear

LED driver 220-240V-50/60Hz included


01. Select version



CORA / C 2



bOPTICS - Symmetric reflector 48°



UGR	W	lm output	lm/W	Lmm	CODE*
≤10	18	2272	126	597	90728L260▼▲◆♦00
≤10	30	3779	126	897	90728L290▼▲◆♦00
≤10	39	5286	136	1197	90728L212▼▲◆♦00
≤10	50	6816	136	1497	90728L215▼▲◆♦00

*Replace the symbols to complete the code

Control gear

HF	E
DALI	H


Colour

□ White	W
■ Black	B


Emergency

No EM	0
EM 3h (K3) ¹	3

CORA / C 3



bOPTICS - Symmetric reflector 48°




UGR	W	lm output	lm/W	CODE*
≤10	26	3408	131	90728Q360▼▲◆♦00


Colour temp.

3000K	3
4000K	0

CORA / C 4



bOPTICS - Symmetric reflector 48°



UGR	W	lm output	lm/W	CODE*
≤10	34	4544	134	90728Q460▼▲◆♦00


¹ Prepared for emergency remote control.

02. Select options


OPTIONS	Code
Low Output version <ul style="list-style-type: none">• Under request.	



Product details



Ceiling surface application



bOPTICS diffuser

