

## DYNA IP



### Product characteristics

#### Body

Aluminium



#### Finish

Powder coated



#### Optical system

Opal tempered glass



#### Light source

LED, RG1, CRI>80, MacAdam Step ≤3

#### LED lifetime

60.000h @ L70, B10, Ta 25°C



#### Control gear


Not included

#### Ceiling thickness


For ceilings between 1-20 mm

## 01. Select version

### DYNA IP



#### Opal tempered glass



W	lm output	lm/W	mA	Φ	CODE*
17	2326	138	500	Ø215	90136L00L0♣0♦00
24	3121	129	700	Ø215	90136L00M0♣0♦00
32	3884	121	900	Ø215	90136L00H0♣0♦00



\*Replace the symbols to complete the code

Colour	Symbol
White	♣
Black	♠

Colour temp.	Symbol
3000K	♦
4000K	0

### DYNA IP

• To complete the product add the control gear. Please order separately.

## 02. Select options



### Product details

#### OPTIONS Code

##### Control gear HF

Driver 21W 10-42V 500mA HF	900007E
Driver 28W 28-40V 700mA HF	900303E
Driver 37,8W 30-42V 900mA HF	900500E

##### Control gear dimmable DALI

Driver 26W 09-52V 500MA DALI+ PUSH	900107H
Driver 26,3W 09-37,5V 700mA DALI+ PUSH	900111H
Driver 44,1W 09-49V 900mA DALI+ PUSH	900604H

##### Steel safety cable

L1500 mm	955000
----------	--------

##### Emergency unit (3 hours)

• Under request.



Brackets