

DYNA MINI Sq



Product characteristics

Body

Steel sheet

Finish

Powder coated

Optical system

PM - Matte reflector

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

50.000h @ L80, B10, Ta 25°C

Control gear

Not included


Ceiling thickness

For ceilings between 1-25 mm




01. Select version

DYNA MINI Sq



PM - Matte reflector



W	lm output	lm/W	mA	□	CODE*
8	1297	157	250	165x160	90760L00L0♣0♦00
17	2505	150	500	165x160	90760L00M0♣0♦00
24	3396	142	700	165x160	90760L00H0♣0♦00



*Replace the symbols to complete the code

Colour	♣
□ White	W
■ Black	B

Colour temp.	♦
3000K	B
4000K	A

DYNA MINI Sq

• To complete the product add the control gear. Please order separately.

02. Select options



Product details

OPTIONS Code

Control gear HF

Driver 10,5W 10-42V 250mA HF	900002E
Driver 21W 10-42V 500mA HF	900007E
Driver 28W 28-40V 700mA HF	900303E

Control gear dimmable DALI

Driver 13W 09-52V 250mA DALI+ PUSH	900102H
Driver 26W 09-52V 500mA DALI+ PUSH	900107H
Driver 26,3W 09-37,5V 700mA DALI+ PUSH	900111H

Steel safety cable

L1500 mm	955000
----------	--------



Downlight



Front view