

DYNA MINI



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

PM - Matte reflector

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

50.000h @ L80, B10, Ta 25°C

Control gear

Not included

Ceiling thickness


For ceilings between 1-20 mm




01. Select version



DYNA MINI



PM - Matte reflector



W	lm output	lm/W	mA	Ø	CODE*
8	1064	129	250	Ø155	90183L00L0♣0♦00
17	2125	128	500	Ø155	90183L00M0♣0♦00
24	2881	120	700	Ø155	90183L00H0♣0♦00

*Replace the symbols to complete the code

Colour	Symbol
White	♣
Black	♠

Colour temp.	Symbol
3000K	♦
4000K	♠

DYNA MINI

• To complete the product add the control gear. Please order separately.

02. Select options



Product details

OPTIONS Code

Control gear HF

Driver 10,5W 10-42V 250mA HF	900002E
Driver 21W 10-42V 500mA HF	900007E
Driver 28W 28-40V 700mA HF	900303E

Control gear dimmable DALI

Driver 13W 09-52V 250mA DALI+ PUSH	900102H
Driver 26W 09-52V 500mA DALI+ PUSH	900107H
Driver 26,3W 09-37,5V 700mA DALI+ PUSH	900111H

Steel safety cable

L1500 mm	955000
----------	--------



Downlight



Front view