

ELI 50 Sq



Product characteristics

Body

Aluminium

**Finish**

Powder coated

230V/50Hz

Optical system

PB - Shiny reflector



IP 20

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

60.000h @ L80, B10, Ta 25°C


650°C

Control gear


LED driver 220-240V-50/60Hz included

01. Select version

ELI 50 Sq




PB - Shiny reflector - 20°



W	lm output	lm/W	CODE*
7	747	107	90687L240▼▲0◆20
11	1168	106	90686L240▼▲0◆20

PB - Shiny reflector - 50°



W	lm output	lm/W	CODE*
7	724	103	90687L240▼▲0◆50
11	1144	104	90686L240▼▲0◆50



*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour	
□ White	W
■ Black	B

Colour temp.	
3000K	3
4000K	0

ELI 50 Sq

• To complete the product add the current supply cable and the ceiling rose. Please order separately.

02. Select options



*Replace the symbols to complete the code

OPTIONS Code*

Transparent current supply cable

L1500 mm - 3 x 0,75 mm ²	940400
L1500 mm - 5 x 0,75 mm ²	940500
L3000 mm - 3 x 0,75 mm ²	940401
L3000 mm - 5 x 0,75 mm ²	940501
L6000 mm - 3 x 0,75 mm ²	940402
L6000 mm - 5 x 0,75 mm ²	940507


Square ceiling rose

Surface T46 Q50	47 50	978807▲
Recessed T47 Q50	Ø40 32 50	978808▲

Colour	
□ White	W
■ Black	B



Product details



Ceiling rose