

ELI Sq /E 1



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

PB - Shiny reflector

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

50.000h @ L90, B10, Ta 25°C

Control gear

Not included

Ceiling thickness


For ceilings between 1-25 mm




01. Select version



ELI Sq /E 1




PB - Shiny reflector - 35°



UGR	W	lm output	lm/W	mA	Ø	CODE*
≤19	5	706	141	150	Ø95	90673L0010▲0♦35
≤19	8	1161	145	250	Ø95	90655L0010▲0♦35

CO - C180 —
C90 - C270 - -

PB - Shiny reflector - 60°



UGR	W	lm output	lm/W	mA	Ø	CODE*
≤22	5	706	141	150	Ø95	90673L0010▲0♦60
≤22	8	1161	145	250	Ø95	90655L0010▲0♦60

CO - C180 —
C90 - C270 - -

*Replace the symbols to complete the code

Colour	Symbol
White	W
Black	B

Colour temp.	Symbol
3000K	3
4000K	0

ELI Sq /E 1

• To complete the product add the control gear. Please order separately.

02. Select options

OPTIONS Code

Control gear HF

Driver 6,3W 10-42V 150mA HF	900000E
Driver 10,5W 10-42V 250mA HF	900002E

Control gear dimmable DALI

Driver 7,8W 09-52V 150mA DALI+ PUSH	900100H
Driver 13W 09-52V 250mA DALI+ PUSH	900102H

Steel safety cable

L1500 mm	955010
----------	--------

ELI Sq /E 2



Product characteristics

Body

Aluminium

**Finish**

Powder coated

**Optical system**

PB - Shiny reflector

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

**LED lifetime**

50.000h @ L90, B10, Ta 25°C

Control gear

Not included


Ceiling thickness

For ceilings between 1-25 mm


01. Select version



ELI Sq /E 2




PB - Shiny reflector - 35°



UGR	W	lm output	lm/W	mA	Ø	CODE*
≤19	10	1411	141	300	Ø95x195	90673L0020▲0♦35
≤19	16	2322	145	500	Ø95x195	90655L0020▲0♦35

PB - Shiny reflector - 60°



UGR	W	lm output	lm/W	mA	Ø	CODE*
≤22	10	1411	141	300	Ø95x195	90673L0020▲0♦60
≤22	16	2322	145	500	Ø95x195	90655L0020▲0♦60

*Replace the symbols to complete the code

Colour	Symbol
White	W
Black	B

Colour temp.	Symbol
3000K	3
4000K	0

ELI Sq /E 2

• To complete the product add the control gear. Please order separately.

02. Select options

OPTIONS Code

Control gear HF

Driver 12,6W 10-42V 300mA HF	900003E
Driver 21W 10-42V 500mA HF	900007E

Control gear dimmable DALI

Driver 15,6W 09-52V 300mA DALI+ PUSH	900103H
Driver 26W 09-52V 500mA DALI+ PUSH	900107H

Steel safety cable

L1500 mm	955010
----------	--------