

ELI Sq



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

PB - Shiny reflector

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

50.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz




IP 20


650°C

01. Select version

ELI Sq




PB - Shiny reflector - 35°



UGR	W	lm output	lm/W	CODE*
≤19	6	706	118	90676L200▼▲0◆35
≤19	9	1161	129	90566L200▼▲0◆35

PB - Shiny reflector - 60°



UGR	W	lm output	lm/W	CODE*
≤22	6	706	118	90676L200▼▲0◆60
≤22	9	1161	129	90566L200▼▲0◆60



*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour	
□ White	W
■ Black	B

Colour temp.	
3000K	3
4000K	0

ELI Sq

• To complete the product add the current supply cable and the ceiling rose. Please order separately.

02. Select options



*Replace the symbols to complete the code

OPTIONS Code*

Transparent current supply cable

L1500 mm - 3 x 0,75 mm ²	940400
L1500 mm - 5 x 0,75 mm ²	940500
L3000 mm - 3 x 0,75 mm ²	940401
L3000 mm - 5 x 0,75 mm ²	940501
L6000 mm - 3 x 0,75 mm ²	940402
L6000 mm - 5 x 0,75 mm ²	940507


Square ceiling rose

Surface T25 Q100	45 100	978610▲
Recessed T7 Q90	Ø70 35 90	971400▲

Colour	
□ White	W
■ Black	B



Product details



Ceiling rose