

FESAL Sq IP



Product characteristics

Body

Steel sheet

Finish

Powder coated

Optical system

PB - Shiny reflector
Transparent polycarbonate

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

50.000h @ L80, B10, Ta 25°C

Control gear

Not included

Ceiling thickness


For ceilings between 1-25 mm




01. Select version



FESAL Sq IP



PB - Shiny reflector | Beam angle of 35°




| W | lm output | lm/W | mA | Size | CODE* |
|----|-----------|------|-----|-------|-----------------|
| 8 | 796 | 122 | 200 | 95x93 | 90766L00L0♣0♦35 |
| 14 | 1330 | 113 | 350 | 95x93 | 90766L00H0♣0♦35 |

*Replace the symbols to complete the code

| Colour | Symbol |
|--------|--------|
| White | ♣ |
| Black | ♠ |

| Colour temp. | Symbol |
|--------------|--------|
| 3000K | ♦ |
| 4000K | ♠ |

PB - Shiny reflector | Beam angle of 60°



| W | lm output | lm/W | mA | Size | CODE* |
|----|-----------|------|-----|-------|-----------------|
| 8 | 817 | 125 | 200 | 95x93 | 90766L00L0♣0♦60 |
| 14 | 1347 | 115 | 350 | 95x93 | 90766L00H0♣0♦60 |

FESAL Sq IP

• To complete the product it is necessary to separately order the driver.

02. Select options

OPTIONS Code

Control gear HF

| | |
|------------------------------|---------|
| Driver 8,4W 10-42V 200mA HF | 900001E |
| Driver 14,7W 10-42V 350mA HF | 900004E |

Control gear dimmable DALI

| | |
|--------------------------------------|---------|
| Driver 10,4W 09-52V 200mA DALI+ PUSH | 900101H |
| Driver 18,2W 09-52V 350mA DALI+ PUSH | 900104H |

Steel safety cable

| | |
|----------|--------|
| L1500 mm | 955000 |
|----------|--------|