

FESAL Sq



Product characteristics

Body

Steel sheet

**Finish**

Powder coated

**Optical system**

PB - Shiny reflector

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

**LED lifetime**

50.000h @ L80, B10, Ta 25°C

Control gear

Not included


Ceiling thickness

For ceilings between 1-25 mm


01. Select version



FESAL Sq




PB - Shiny reflector | Beam angle of 35°



| UGR | W | lm output | lm/W | mA | □ | CODE* |
|-----|----|-----------|------|-----|-------|-----------------|
| ≤16 | 8 | 796 | 122 | 200 | 95x93 | 90767L00L0♣0♦35 |
| ≤19 | 14 | 1330 | 113 | 350 | 95x93 | 90767L00H0♣0♦35 |

PB - Shiny reflector | Beam angle of 60°



| UGR | W | lm output | lm/W | mA | □ | CODE* |
|-----|----|-----------|------|-----|-------|-----------------|
| ≤22 | 8 | 817 | 125 | 200 | 95x93 | 90767L00L0♣0♦60 |
| ≤22 | 14 | 1347 | 115 | 350 | 95x93 | 90767L00H0♣0♦60 |

*Replace the symbols to complete the code

| Colour | ♣ |
|---------|---|
| □ White | W |
| ■ Black | B |

| Colour temp. | ♦ |
|--------------|---|
| 3000K | B |
| 4000K | A |

FESAL Sq

• To complete the product add the control gear. Please order separately.

02. Select options

OPTIONS Code

Control gear HF

| | |
|------------------------------|---------|
| Driver 8,4W 10-42V 200mA HF | 900001E |
| Driver 14,7W 10-42V 350mA HF | 900004E |

Control gear dimmable DALI

| | |
|--------------------------------------|---------|
| Driver 10,4W 09-52V 200mA DALI+ PUSH | 900101H |
| Driver 18,2W 09-52V 350mA DALI+ PUSH | 900104H |

Steel safety cable

| | |
|----------|--------|
| L1500 mm | 955000 |
|----------|--------|