

HOLI Sq /AS Max



Product characteristics

Body

Steel sheet

**Finish**

Powder coated

230V/50Hz

Optical system

LIGHT+ - Opal diffuser

**Light source**

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime

60.000h @ L70, B10, Ta 25°C

**Control gear**


Not included

Ceiling thickness


For ceilings between 1-20 mm

01. Select version

HOLI Sq /AS Max



LIGHT+ - Opal diffuser



W	lm output	lm/W	mA	□	CODE*
7	792	113	200	155x155	90393L1060◆0◆◆0
12	1344	112	350	155x155	90393L1100◆0◆◆0



*Replace the symbols to complete the code

Colour	◆/◆
□ White	W/W
■ Black	B/B
▣ White/Black	W/B



Subtitle:

1. Frame
2. Reflector

HOLI Sq /AS Max

• To complete the product add the control gear. Please order separately.

Colour temp.	◆
3000K	3
4000K	0

02. Select options

OPTIONS Code

Control gear HF

Driver 8,4W 10-42V 200mA HF	900001E
Driver 14,7W 10-42V 350mA HF	900004E

Control gear dimmable DALI

Driver 10,4W 09-52V 200mA DALI+ PUSH	900101H
Driver 18,2W 09-52V 350mA DALI+ PUSH	900104H

Steel safety cable

L1500 mm	955000
----------	--------



Product details



Finish in white colour



Finish in black colour



Finish in white/black colour