

## HOLI Sq Max



### Product characteristics

**Body**  
Steel sheet

**Finish**  
Powder coated


**Optical system**  
PRISM+ - Microprismatic diffuser  
LIGHT+ - Opal diffuser

**Light source**  
LED, RG1, CRI>80, MacAdam Step  $\leq 3$

**LED lifetime**  
60.000h @ L70, B10, Ta 25°C


**Control gear**  
Not included

**Ceiling thickness**  
For ceilings between 1-20 mm




## 01. Select version

### HOLI Sq Max




#### PRISM+ - Microprismatic diffuser



W	lm output	lm/W	mA	□	CODE*
8	1010	126	250	155x155	90264L1100♣♣♣0
12	1363	114	350	155x155	90264L1130♣♣♣0
18	1900	106	500	155x155	90264L1170♣♣♣0

#### LIGHT+ - Opal diffuser



W	lm output	lm/W	mA	□	CODE*
8	1120	140	250	155x155	90295L1100♣♣♣0
12	1533	128	350	155x155	90295L1130♣♣♣0
18	2082	116	500	155x155	90295L1170♣♣♣0



\*Replace the symbols to complete the code

Colour	♣/♠
□ White	W/W
■ Black	B/B
▣ White/Black	W/B



Subtitle:

1. Frame
2. Reflector

Colour temp.	♠
3000K	3
4000K	0

### HOLI Sq Max

• To complete the product add the control gear. Please order separately.

## 02. Select options

### OPTIONS Code

#### Control gear HF

Driver 10,5W 10-42V 250mA HF	900002E
Driver 14,7W 10-42V 350mA HF	900004E
Driver 21W 10-42V 500mA HF	900007E

#### Control gear dimmable DALI

Driver 13W 09-52V 250mA DALI+ PUSH	900102H
Driver 18,2W 09-52V 350mA DALI+ PUSH	900104H
Driver 26W 09-52V 500mA DALI+ PUSH	900107H

#### Steel safety cable

L1500 mm	955000
----------	--------



### Product details



Finish in white colour



Finish in black colour



Finish in white/black colour