

HOLI Sq Mini



Product characteristics

Body

Steel sheet

Finish

Powder coated

Optical system

PRISM+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime

60.000h @ L70, B10, Ta 25°C

Control gear

Not included

Ceiling thickness

For ceilings between 1-20 mm



230V/50Hz




IP 40

650°C




01. Select version

HOLI Sq Mini




PRISM+ - Microprismatic diffuser



W	lm output	lm/W	mA	Size	CODE*
7	759	115	200	97x97	90258L1070▲0◆▲0

LIGHT+ - Opal diffuser



W	lm output	lm/W	mA	Size	CODE*
7	837	120	200	97x97	90293L1070▲0◆▲0



*Replace the symbols to complete the code

Colour	Symbol
White	W/W
Black	B/B
White/Black	W/B



Subtitle:

1. Frame
2. Reflector

Colour temp.	Symbol
3000K	3
4000K	0

HOLI Sq Mini

• To complete the product add the control gear. Please order separately.

02. Select options

OPTIONS	Code
Control gear HF Driver 8,4W 10-42V 200mA HF	900001E
Control gear dimmable DALI Driver 10,4W 09-52V 200mA DALI+ PUSH	900101H
Steel safety cable L1500 mm	955000



Product details



Finish in white colour



Finish in black colour



Finish in white/black colour