

## HOLI Sq /T



### Product characteristics

---

**Body**

Steel sheet

**Finish**

Powder coated

**Fixing system**

Trimless mounting kit

**Optical system**

PRISM+ - Microprismatic diffuser  
LIGHT+ - Opal diffuser

**Light source**

LED, RG1, CRI>80, MacAdam Step  $\leq 3$

**LED lifetime**

60.000h @ L70, B10, Ta 25°C

**Control gear**

Not included

---



230V/50Hz




650°C




## 01. Select version



### HOLI Sq /T




#### PRISM+ - Microprismatic diffuser



W	lm output	lm/W	mA	Size	CODE*
7	748	107	200	114x114	90223L1060♣0♦00
8	927	116	250	114x114	90223L1100♣0♦00

#### LIGHT+ - Opal diffuser



W	lm output	lm/W	mA	Size	CODE*
7	826	118	200	114x114	90272L1060♣0♦00
8	1023	128	250	114x114	90272L1100♣0♦00

\*Replace the symbols to complete the code

Colour	Symbol
White	♣
Black	♠

Colour temp.	Symbol
3000K	♦
4000K	0

### HOLI Sq /T

• To complete the product add the control gear and trimless mounting kit. Please order separately.

## 02. Select options



### Product details

#### OPTIONS Code

##### Control gear HF


Driver 8,4W 10-42V 200mA HF	900001E
Driver 10,5W 10-42V 250mA HF	900002E

##### Control gear dimmable DALI

Driver 10,4W 09-52V 200mA DALI+ PUSH	900101H
Driver 13W 09-52V 250mA DALI+ PUSH	900102H

##### Trimless mounting kit

White	971501
-------	--------



##### Steel safety cable

L1500 mm	955000
----------	--------



Finish in white colour



Finish in black colour