

HOLI Sq



Product characteristics

Body

Steel sheet

Finish

Powder coated

Optical system

PRISM+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime

60.000h @ L70, B10, Ta 25°C

Control gear

Not included

Ceiling thickness

For ceilings between 1-20 mm



230V/50Hz




IP 40

650°C




01. Select version

HOLI Sq




PRISM+ - Microprismatic diffuser



W	lm output	lm/W	mA	□	CODE*
7	748	107	200	115x115	90259L1060♣0♣♣0
8	927	116	250	115x115	90259L1100♣0♣♣0

LIGHT+ - Opal diffuser



W	lm output	lm/W	mA	□	CODE*
7	826	118	200	115x115	90294L1060♣0♣♣0
8	1023	128	250	115x115	90294L1100♣0♣♣0



*Replace the symbols to complete the code

Colour	♣/♣
□ White	W/W
■ Black	B/B
▣ White/Black	W/B



Subtitle:

1. Frame
2. Reflector

Colour temp.	♠
3000K	3
4000K	0

HOLI Sq

• To complete the product add the control gear. Please order separately.

02. Select options

OPTIONS	Code
Control gear HF	
Driver 8,4W 10-42V 200mA HF	900001E
Driver 10,5W 10-42V 250mA HF	900002E
Control gear dimmable DALI	
Driver 10,4W 09-52V 200mA DALI+ PUSH	900101H
Driver 13W 09-52V 250mA DALI+ PUSH	900102H
Steel safety cable	
L1500 mm	955000



Product details



Finish in white colour



Finish in black colour



Finish in white/black colour