

OREO /C



Product characteristics

Body

Aluminium



Finish

Powder coated



Optical system

bLINE - Opal diffuser

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3



LED lifetime

60.000h @ L80, B10, Ta 25°C


Control gear

LED driver 220-240V-50/60Hz included


01. Select version



OREO /C



In/Out | bLINE - Opal diffuser




W
51

lm output
1697

lm/W
33

CODE*
90423L630▼▲0●00

Out | bLINE - Opal diffuser



W
31

lm output
1100

lm/W
35

CODE*
90422L630▼▲0●00

*Replace the symbols to complete the code

Control gear ▼

HF	E
DALI	H
SwitchDIM ¹	O
OC	T

Colour ² ▲

□ White	W
■ Grey	G
■ Black	B
■ Sahara	0
■ Mist	1
■ Carbon	I
■ Autumn	L
■ Rusty chain	R
■ Jungle	N
■ Golden eye	D
■ Old rose	5
■ Copper	7

Colour temp. ●

2700K	2
3000K	3
4000K	0
Tunable White ³	T
RGB White ⁴	R



Product details



bLINE diffuser



Clip-in diffuser

¹ Only available for In/Out versions of 2700K, 3000K or 4000K.

² See page 212.

³ Tunable White (3000K - 5700K). Only available with OC OmniaControl Driver.

⁴ RGB White (2700K). Only available with OC OmniaControl Driver.