

OREO In



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

bLINE - Opal diffuser

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

60.000h @ L80, B10, Ta 25°C

Control gear


Not included




01. Select version



OREO In



bLINE - Opal diffuser



W	lm output	lm/W	Dmm	CODE*
26	1378	53	Ø650	90400L6500▲0◆00
38	2067	54	Ø970	90400L9700▲0◆00
50	2687	54	Ø1255	90400L1250▲0◆00
61	3307	54	Ø1540	90400L1540▲0◆00
78	4203	54	Ø1955	90400L1950▲0◆00

*Replace the symbols to complete the code

Colour ¹	Symbol
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D
Old rose	5
Copper	7

OREO In

- Current supply cable/suspension with 1500 mm included.
- To complete the product add ceiling rose. Please order separately.
- For RGB White versions, the product must include a transparent current supply cable.

Colour temp.	Symbol
2700K	2
3000K	3
4000K	0
Tunable White ²	T
RGB White ³	R

¹ See page 212.

² Tunable White (3000K - 5700K). Only available with ceiling rose TW + OmniaControl.

³ RGB White (2700K). Only available with ceiling rose RGB White + OmniaControl.

02. Select ceiling rose



Trimless

50 l  Ø120

 Ø128

HF

	CODE*
Ø650	975800 
Ø970, Ø1255	975801 
Ø1540, Ø1955	975803 

DALI

	CODE*
Ø650	975900 
Ø970, Ø1255	975901 
Ø1540, Ø1955	975903 

OmniaControl

	CODE*
Ø650	976000 
Ø970, Ø1255	976001 
Ø1540, Ø1955	976003 

RGB White + OmniaControl

	CODE*
Ø650, Ø970	976005 
Ø1255	976007 
Ø1540	976008 
Ø1955	976009 

Tunable White + OmniaControl

	CODE*
Ø650, Ø970	976010 
Ø1255	976012 
Ø1540	976013 
Ø1955	976014 

Recessed

82 l  Ø150

 Ø128

HF

	CODE*
Ø650	975500 
Ø970, Ø1255	975501 
Ø1540, Ø1955	975503 

DALI

	CODE*
Ø650	975600 
Ø970, Ø1255	975601 
Ø1540, Ø1955	975603 

OmniaControl

	CODE*
Ø650	975700 
Ø970, Ø1255	975701 
Ø1540, Ø1955	975703 

RGB White + OmniaControl

	CODE*
Ø650, Ø970	975705 
Ø1255	975707 
Ø1540	975708 
Ø1955	975709 

Tunable White + OmniaControl

	CODE*
Ø650, Ø970	975710 
Ø1255	975712 
Ø1540	975713 
Ø1955	975714 

Surface mounted

41,5 l  Ø400

HF

	CODE*
Ø650	975200 
Ø970, Ø1255	975201 
Ø1540, Ø1955	975203 

DALI

	CODE*
Ø650	975300 
Ø970, Ø1255	975301 
Ø1540, Ø1955	975303 

OmniaControl

	CODE*
Ø650	975400 
Ø970, Ø1255	975401 
Ø1540, Ø1955	975403 

RGB White + OmniaControl

	CODE*
Ø650, Ø970	975405 
Ø1255	975407 
Ø1540	975408 
Ø1955	975409 

Tunable White + OmniaControl

	CODE*
Ø650, Ø970	975410 
Ø1255	975412 
Ø1540	975413 
Ø1955	975414 

*Replace the symbols to complete the code

Colour 
 White **W**
 Black **B**

CEILING ROSE

- Control gear included in the ceiling rose.
- The trimless recessed ceiling rose is class III.
- The surface ceiling rose is class I.

Product details



bLINE diffuser



Clip-in diffuser



Trimless recessed ceiling rose



Recessed ceiling rose



Surface ceiling rose



Photo: Pedro Sampayo Ribeiro