

## OREO Out



### Product characteristics

---

**Body**

Aluminium

**Finish**

Powder coated

**Optical system**

bLINE - Opal diffuser

**Light source**

LED, RG1, CRI>90, MacAdam Step ≤3

**LED lifetime**

60.000h @ L80, B10, Ta 25°C

**Control gear**

Not included


---




# 01. Select version



## OREO Out



### bLINE - Opal diffuser



W	lm output	lm/W	Dmm	CODE*
23	1310	57	Ø630	90401L6300▲0◆00
36	2038	57	Ø950	90401L9500▲0◆00
49	2766	56	Ø1270	90401L1270▲0◆00
60	3422	57	Ø1555	90401L1550▲0◆00
77	4368	57	Ø1970	90401L1970▲0◆00

\*Replace the symbols to complete the code

Colour <sup>1</sup>	Symbol	Code
White	□	W
Grey	■	G
Black	■	B
Sahara	■	0
Mist	■	1
Carbon	■	I
Autumn	■	L
Rusty chain	■	R
Jungle	■	N
Golden eye	■	D
Old rose	■	5
Copper	■	7

## OREO Out

- Current supply cable/suspension with 1500 mm included.
- To complete the product add ceiling rose. Please order separately.
- For RGB White versions, the product must include a transparent current supply cable.

Colour temp.	Symbol	Code
2700K	◆	2
3000K	◆	3
4000K	◆	0
Tunable White <sup>2</sup>	◆	T
RGB White <sup>3</sup>	◆	R

<sup>1</sup> See page 212.

<sup>2</sup> Tunable White (3000K - 5700K). Only available with ceiling rose TW + OmniaControl.

<sup>3</sup> RGB White (2700K). Only available with ceiling rose RGB White + OmniaControl.

## 02. Select ceiling rose






### Trimless




50 l  Ø120

 Ø128




#### HF

	CODE*
Ø630	975800 
Ø950, Ø1270	975801 
Ø1555, Ø1970	975803 





#### DALI

	CODE*
Ø630	975900 
Ø950, Ø1270	975901 
Ø1555, Ø1970	975903 





#### OmniaControl

	CODE*
Ø630	976000 
Ø950, Ø1270	976001 
Ø1555, Ø1970	976003 

#### RGB White + OmniaControl

	CODE*
Ø630, Ø950	976005 
Ø1270	976007 
Ø1555	976008 
Ø1970	976009 

#### Tunable White + OmniaControl




	CODE*
Ø630, Ø950	976010 
Ø1270	976012 
Ø1555	976013 
Ø1970	976014 

### Recessed




82 l  Ø150

 Ø128




#### HF

	CODE*
Ø630	975500 
Ø950, Ø1270	975501 
Ø1555, Ø1970	975503 





#### DALI

	CODE*
Ø630	975600 
Ø950, Ø1270	975601 
Ø1555, Ø1970	975603 





#### OmniaControl

	CODE*
Ø630	975700 
Ø950, Ø1270	975701 
Ø1555, Ø1970	975703 

#### RGB White + OmniaControl

	CODE*
Ø630, Ø950	975705 
Ø1270	975707 
Ø1555	975708 
Ø1970	975709 




#### Tunable White + OmniaControl

	CODE*
Ø630, Ø950	975710 
Ø1270	975712 
Ø1555	975713 
Ø1970	975714 




### Surface mounted

41,5 l  Ø400




#### HF

	CODE*
Ø630	975200 
Ø950, Ø1270	975201 
Ø1555, Ø1970	975203 





#### DALI

	CODE*
Ø630	975300 
Ø950, Ø1270	975301 
Ø1555, Ø1970	975303 





#### OmniaControl

	CODE*
Ø630	975400 
Ø950, Ø1270	975401 
Ø1555, Ø1970	975403 


#### RGB White + OmniaControl

	CODE*
Ø630, Ø950	975405 
Ø1270	975407 
Ø1555	975408 
Ø1970	975409 

#### Tunable White + OmniaControl

	CODE*
Ø630, Ø950	975410 
Ø1270	975412 
Ø1555	975413 
Ø1970	975414 

\*Replace the symbols to complete the code

Colour   
 White W  
 Black B

### CEILING ROSE

- Control gear included in the ceiling rose.
- The trimless recessed ceiling rose is class III.
- The surface ceiling rose is class I.


### Product details



bLINE diffuser



Clip-in diffuser



Trimless recessed ceiling rose



Recessed ceiling rose



Surface ceiling rose

