

OREO V In



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

bLINE - Opal diffuser

Light source

LED, RG1, CRI>90, MacAdam Step ≤ 3

LED lifetime

60.000h @ L80, B10, Ta 25°C

Control gear


Not included




01. Select version



OREOV In



bLINE - Opal diffuser



W	lm output	lm/W	Dmm	CODE*
26	1378	53	Ø650	90425L6500▲0◆00
38	2067	54	Ø970	90425L9700▲0◆00
50	2687	54	Ø1255	90425L1250▲0◆00
61	3307	54	Ø1540	90425L1540▲0◆00
78	4203	54	Ø1955	90425L1950▲0◆00

*Replace the symbols to complete the code

Colour ¹	Symbol
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D
Old rose	5
Copper	7

OREOV In

- Current supply cable/suspension with 1500 mm included.
- To complete the product add ceiling rose. Please order separately.
- For Ø1540 and Ø1955 mm versions, the product must include a transparent power cable.
- For Tunable White and RGB White versions, the product must include a transparent current supply cable.

Colour temp.	Symbol
2700K	2
3000K	3
4000K	0
Tunable White ²	T
RGB White ³	R

¹ See page 212.

² Tunable White (3000K - 5700K). Only available with ceiling rose TW + OmniaControl.

³ RGB White (2700K). Only available with ceiling rose RGB White + OmniaControl.

02. Select ceiling rose



*Replace the symbols to complete the code




Colour  White **W**
 Black **B**

Trimless




50 |  Ø120

 Ø128




HF

	CODE*
Ø650	976700 
Ø970, Ø1255	976701 
Ø1540, Ø1955	976703 




DALI

	CODE*
Ø650	976800 
Ø970, Ø1255	976801 
Ø1540, Ø1955	976803 




OmniaControl

	CODE*
Ø650	976900 
Ø970, Ø1255	976901 
Ø1540, Ø1955	976903 

RGB White + OmniaControl

	CODE*
Ø650, Ø970	976905 
Ø1255, Ø1540	976907 
Ø1955	976909 

Tunable White + OmniaControl




	CODE*
Ø650, Ø970	976910 
Ø1255, Ø1540	976912 
Ø1955	976914 

Recessed




82 |  Ø150

 Ø128




HF

	CODE*
Ø650	976400 
Ø970, Ø1255	976401 
Ø1540, Ø1955	976403 




DALI

	CODE*
Ø650	976500 
Ø970, Ø1255	976501 
Ø1540, Ø1955	976503 




OmniaControl

	CODE*
Ø650	976600 
Ø970, Ø1255	976601 
Ø1540, Ø1955	976603 

RGB White + OmniaControl

	CODE*
Ø650, Ø970	976605 
Ø1255, Ø1540	976607 
Ø1955	976609 

Tunable White + OmniaControl




	CODE*
Ø650, Ø970	976610 
Ø1255, Ø1540	976612 
Ø1955	976614 

Surface mounted



a) 270
135 |  44

b) 320
145 |  44




HF

	CODE*
Ø650 ^{a)}	976100 
Ø970, Ø1255 ^{a)}	976101 
Ø1540, Ø1955 ^{b)}	976103 



DALI

	CODE*
Ø650 ^{a)}	976200 
Ø970, Ø1255 ^{a)}	976201 
Ø1540, Ø1955 ^{b)}	976203 





OmniaControl

	CODE*
Ø650 ^{a)}	976300 
Ø970, Ø1255 ^{a)}	976301 
Ø1540, Ø1955 ^{b)}	976303 

RGB White + OmniaControl

	CODE*
Ø650, Ø970 ^{a)}	976305 
Ø1255 ^{a)}	976307 
Ø1540 ^{b)}	976308 
Ø1955 ^{b)}	976309 

Tunable White + OmniaControl

	CODE*
Ø650, Ø970 ^{a)}	976310 
Ø1255 ^{a)}	976312 
Ø1540 ^{b)}	976313 
Ø1955 ^{b)}	976314 

CEILING ROSE

- Control gear included in the ceiling rose.
- The trimless recessed ceiling rose is class III.
- The surface ceiling rose is class I.


Product details




bLINE diffuser




Clip-in diffuser



Trimless recessed ceiling rose



Recessed ceiling rose



Surface ceiling rose

